

High voltage discharge rod EST

For damped discharge and direct, visible earthing



- Available for multiple voltage ranges
- For safe discharging and earthing of cables and test units

DESCRIPTION

When conducting dielectric tests on cables or doing fault location measurements with high DC voltages, the cable capacitance is charged and represents a dangerous amount of energy. The charging energy is calculated by the formula:

$$2 P = U^2 \cdot \frac{C}{2}$$

Hence, after a measurement, the cable under test must be subjected to a damped discharge and a direct, visible earthing. Instructions and recommendations for discharging, earthing and short circuiting can be found in the following VDE regulations:

- DIN EN 50191 / VDE 0104 01/01
- DIN VDE 0105-100 06/2000
- DIN EN 61230 91/96
- DIN EN 61219 01/95

The discharge time is calculated by the formula:

$$\tau = R C \text{ (s / M}\Omega \text{ / }\mu\text{F)}$$

After 5 - 10 τ (max. 5 s) the voltage drops to a harmless value. Now the cable can be visibly short-circuited by means of the earthing hook.

The Megger discharge rod touches the live wire with a tip that features a discharge resistor that limits the discharge current and ensures a damped discharge. Within a split second most of the cable's charge has flown off, eliminating the post-charging effect. The discharge rods are made of GFK (fibre-glass strengthened plastic). They are equipped with grip protection with extra-long safety clearance against physical contact with high voltage.

Application

Take care that the correct number of discharge resistors are screwed together. Before using the discharge rod, the earthing cable has to be connected to safety or an operational earth. Before using the hook to earth the cable, it should be discharged via the tip of the rod for a couple of seconds.

Important note

The Megger discharge rods are designed only for the discharge of high voltage cables within the framework of cable tests. After use, allow a cooling period of 30 minutes to avoid a thermal overload of the built-in discharge resistors.

TECHNICAL DATA*

	kV	Length	Weight	max. Capacity	R
EST 0	–	152 cm	1.40 kg	–	–
EST 35	35 kV	50 cm	0.95 kg	6 µF	10 kΩ
EST 50	50 kV	136 cm	1.90 kg	6 µF	100 kΩ
EST 75	80 kV	156 cm	2.20 kg	3 µF	150 kΩ
EST 100	110 kV	176 cm	2.50 kg	2 µF	200 kΩ
EST 150	150 kV	208 cm	2.85 kg	2 µF	300 kΩ

ORDERING INFORMATION

Product	Order no.
EST 0	810000058
EST 35	810300
EST 50	810003725
EST 75	810326
EST 100	810327
EST 150	810000059

* We reserve the right to make technical changes.

GERMANY

Megger GmbH
Obere Zeil 2
D-61440 Oberursel
T +49 6171 92987 0
F +49 6171 92987 19
info@megger.de

Seba Dynatronic
Mess- und Ortungstechnik GmbH
Dr.-Herbert-lann-Str. 6
96148 Baunach
T +49 (0) 9544 680
F +49 (0) 9544 2273
team.dach@megger.de

Hagenuk KMT
Kabelmesstechnik GmbH
Röderaue 41
01471 Radeburg
T +49 (0) 35208 840
F +49 (0) 35208 84249
team.dach@megger.de

CERTIFICATION ISO

Registered to ISO 9001 Cert. no. 000677 QM08

DISCHARGEROD_DS_EN_V01

www.megger.de

Megger is a registered trademark