



YG60S—60°economic gloss meter

YG60S gloss meter is our independently developed gloss meter product with independent intellectual property rights. It is a gloss measuring instrument designed and manufactured with reference to the international standard ISO2813 and the Chinese national standard GB/T9754. It has the function of automatically checking the calibration board.



PRODUCT FEATURES

1. Elegant Design combined with aesthetics and ergonomics
2. With auto-calibration function
3. Meet the working requirements of JJG696 standard
4. Auto Power-off within optional 30-120 seconds
5. Comply to ISO2813,ASTM523, GB/T9754



APPLICATION INDUSTRY

YG60S 60° Economic Gloss Meter , apply to paint, ink, stoving varnish, coating, wood products; marble, granite, vitrified polished tile, pottery brick and porcelain; plastic, paper; hardware industries, etc. for gloss measurement and gloss data transmission.



Automobile




Leather



Plastic




Metal



Stone material



Coating



Others

TECHNICAL SPECIFICATIONS

Measuring Angle:60°

Measuring Range: 0-200GU

Measuring Area: 9x15mm

Division Value:1GU

Measuring Modes:Basic mode

Measuring Time:0.5S

Repeatability:0~100GU : ±0.5GU; 100~2000GU : ±0.5%GU

Accurate: Meet the working requirements of JJG696 standard

Auto Power-off Time:30s

Language:Chinese & English

Display:2.3 inch white and black screen

Size:160*52*84mm

Weight:About 300g

Power Supply:1pc dry-cell battery(can measure 10000 times) or use USB Charge

Interface:USB

Operation Temperature Range:0-40°C(32-104° F)

Storage Temperature Range:-20-50°C(-4-122° F)

Humidity Range:< 85% RH, without condensation

Standard Accessories:User manual, calibration plate

Optional Accessories:Miniature printer

Notification: the technical parameter is only for reference



SHENZHEN ThreeNH TECHNOLOGY CO.,LTD.

Address:F/6, Block 5B, Skyworth Inno Valley, Tangtou 1st Road,
Shiyan, Baoan District, Shenzhen, P.R. China

Service Hotline: 400-666-2522

Email: 3nh@3nh.com

Tel: 86-0755-26508999

Fax: 86-0755-27190609