-25℃ Biomedical Freezer FSF-25V100

Integrated design of cold shelf and evaporator provides additional refrigeration efficiency.

This products designed to store vaccines blood plasma, and many other biological materials, Installations can be found in researching institution and clinical sites in life science, electronic testing and medical markets.

Features

- High density foam insulation for rigidity and stable storage temperature. Microprocessor control, digital display adjustable temperature rage: -10 ℃--25 ℃.
- LED digital display for clear observation.
- Wide voltage tolerance design with applicable voltage range of 187~242 V/AC.

Safety

- Multiple malfunction alarms including high and low temperature, sensor error
- Two types of alarm indications: audible buzzing and visible flashing light.
- Door lock for storage safety

Humanized design

- Upright side door with limit door hinge to prevent collision when door open.
- Controller password protect function to avoid change running parameter randomly.

Certificate:

ISO14001.ISO9001.ISO13485.ISO45001.,FDA List

Warranty:

• 1 year free spare parts and remote technical support.

Special:

Mini cabinet, easy to move.

Lockable design prevents unauthorized access.

Performance		
Temperature Range	-10℃~-25°C	
Ambient Temperature	+10~+32°C	
Controller	Microprocessor	
Display	Digital Display	

Electrical Data		
Power Supply(V/Hz)	220~240V/50~60;115/60	
Rated Power(W)	150	
Electrical Current(A)	0.9	
Power Consumption	2.2 kWh/24h	
Power failure alarm	8H	

Refrigeration System		
Compressor/Brand	1/China Brand	
Refrigerant	R600a	
Cooling Type	Direct cooling	
Defrost Type	Manual	

Dimensions		
Capacity	100L	
Interior Size(W*D*H)	410X410X670mm	
Exterior Size(W*D*H)	540*540*880mm	
Package Size(W*D*H)	590*590*900mm	
N.t./G.t.(approx)	40/43kg	
Loading Qty(20'/40'/40'H)	54/120/120	

Alarm		
High/Low Temperature	Υ	
Sensor Error	Υ	
Power Failure	Y	
Door ajar	Υ	
Thermostat failure	Y	
Condenser clean	/	

Accessories		
Caster	/	
Remote alarm port	/	
Inner Door	/	
Drawers	4	
Test hole	/	
Data logger	Optional	





Lock



High Quanlity Drawers