

STAINLESS STEEL GLOBE VALVE JIS 10K



Bolted bonnet, Outside screwed and yoke, Yoke Integral with Bonnet, Loose disc, Rising stem, Rising Handwheel, Integral Seat Ring. Flanged ends. Butt-welding ends.

Applicable Class 10K Standards:

Face to Face, JIS B2002

End Flanges, JIS B2210

Test Pressure: (Per JIS B2003 standards)

Shell	20 kgf/cm ² (Water)
Seat	15 kgf/cm ² (Water)
	6 kgf/cm ² (Air)

Material: 201 304 316

Model:	SS304-14G	SS316-16G
1 Body	SCS 13	SCS 14
2 Bonnet	SCS 13	SCS 14
3 Stem	SUS 304	SUS 316
4 Disc	SCS 13	SCS 14
5 Gland	SCS 13	SCS 14
6 Gland Packing	PTFE / GRAPHITE	
7 Hand Wheel	DUCTILE IRON	
8 Gasket	PTFE / GRAPHITE	
9 Bonnet Bolt/Nut	A193-B8 / A194-8	
10 Gland Bolt/Nut	A193-B8 / A194-8	
11 Yoke Sleeve	BRONZE	



DIMENSION

mm

SIZE	inch	1/2	3/4	1	1.1/2	2	2.1/2	3	4	5	6	8	10	12
	mm	15	20	25	40	50	65	80	100	125	150	200	250	300
L End to end		108	117	127	165	203	216	241	292	356	406	495	622	698
H Height		190	195	208	265	275	320	360	415	510	535	600	718	760
D Handle		100	100	125	140	170	180	190	220	290	350	400	500	500