

**3/2 Directional control valves
Indirect controlled solenoid operated poppet valves
Internal thread G1/2, 1/2 NPT
or flanged with NAMUR interface**

Main application: single operated process actuators

TÜV-approval based on IEC 61 508, DIN V 19 251

Statistic proof of process field operation

Valves released for safety systems to SIL 4 or AK 7

Add-on manual override and / or inductive limit switches

**The solenoids are applicable in the protection class
EEx me, EEx md, EEx m, EEx ia for zones 1, 2
(gases), 21 und 22 (dusts) ATEX cat.II 2 GD.**

Additional protection class (FM, CSA): XP, IS, NI

**Rest position in the event of power failure provided
by mechanical return spring**

**Suitable for outdoor installation if equipped with
corresponding solenoid**



Technical data

Medium:

Filtered, non-lubricate and dried compressed air,
instrument air, nitrogen and or other non-flammable neutral,
dry fluids

Operation:

Solenoid operated, directly controlled

Flow direction:

fixed

Port size:

G 1/2, 1/2 NPT, NAMUR interface

Orifice:

ND 8

Flow rate:

1000 l/min (1 bar pressure differential)

Operating pressure:

2 to 8 bar

Temperature:

Fluid: -40 to +60°C, SNBR (Special perbunan)
Ambient: -40 to +60°C (dependent on solenoid)

Mounting:

Optional, preferably vertical

Materials:

Body: stainless steel 1.4404/316, brass 2.0401
Black aluminium 3.0615 anodized
Seat seal: SNBR (Special perbunan)
Inner parts: stainless steel, brass

Protect all connections against the penetration of moisture.


Follow the mounting and operating instruction 7503476.

Ordering information


See page 3

Connectors

See page N/UK 7.7.002



Switching function:
pressure port at 1, 2 or 3



NAMUR interface

3/2 indirect valves

| Symbol | Type | Port size 1, 3 | Port size 2, (3) | Operating pressure (bar) | Material | Weight (kg) | Dimensions No. |
|--------|---------|------------------|------------------|--------------------------|-----------------|-------------|----------------|
| | 9802505 | G 1/4, G1/2 | NAMUR G1/4 | 2 ... 8 | Aluminium | 0,9 | 1 |
| | 9802515 | 1/4-NPT, 1/2 NPT | NAMUR 1/4 NPT | 2 ... 8 | Aluminium | 0,9 | 1 |
| | 9802705 | G 1/4, G1/2 | NAMUR G1/4 | 2 ... 8 | Stainless steel | 1,5 | 1 |
| | 9802715 | 1/4-NPT, 1/2 NPT | NAMUR 1/4 NPT | 2 ... 8 | Stainless steel | 1,5 | 1 |
| | 9802555 | G 1/2 | G 1/2 | 2 ... 8 | Aluminium | 0,6 | 2 |
| | 9802565 | 1/2-NPT | 1/2-NPT | 2 ... 8 | Aluminium | 0,6 | 2 |
| | 9802755 | G 1/2 | G 1/2 | 2 ... 8 | Stainless steel | 1,0 | 2 |
| | 9802765 | 1/2-NPT | 1/2-NPT | 2 ... 8 | Stainless steel | 1,0 | 2 |
| | 9802655 | G 1/2 | G 1/2 | 2 ... 8 | Brass | 1,0 | 2 |
| | 9802665 | 1/2-NPT | 1/2-NPT | 2 ... 8 | Brass | 1,0 | 2 |

Solenoid operators

| | Type | Power consumption | | Rated current | | Protection class | Temperature range Ambient/Fluid °C | Electroport size | Weight (kg) | Dimensions No. | Circuit diagram No. |
|--|----------|-------------------|--------------|---------------|--------------|---|--------------------------------------|------------------------------|-------------|----------------|---------------------|
| | | 24V DC (W) | 230V AC (VA) | 24V DC (mA) | 230V AC (mA) | | | | | | |
| | 0763 *7) | 1,9 | 2,1 *5) | 78 | - | IP00 w/o connector *5) IP65 with connector *5) | -25 ... +60 | DIN EN 175 301-803 Form A | 0,3 | 6 | 1 |
| | 0298 *8) | 3,2 | - | 135 | - | EEx m II T4 *1) IP66 T110°C | -20 ... +70 | 3 m Cable | 0,4 | 7 | 4 |
| | 0299 *8) | - | 4,6 | - | 18 | EEx m II T4 *1) IP66 T110°C | -20 ... +70 | 3 m Cable | 0,4 | 7 | 7 |
| | 4200 *8) | 0,8 | - | 33 | - | EEx me II T5/T6 *2) IP66 T130°C | -40 ... +80 (T5) -40 ... +70 (T6) | M20 X 1,5 *6) | 0,85 | 8 | 4 |
| | 4201 *8) | - | 1,3 | - | 26 | EEx me II T4/T6 *2) IP66 T130°C | -40 ... +80 (T4) -40 ... +55 (T6) | M20 X 1,5 *6) | 0,85 | 8 | 7 |
| | 4600 *8) | 0,8 | - | 33 | - | EEx me II T5/T6 *3) EEx md II T5/T6 *3) | -40 ... +80 (T5) -40 ... +70 (T6) | 1/2 NPT *6) | 0,85 | 9 | 4 |
| | 4602 *8) | 0,8 | - | 33 | - | IP66 T130°C | | M20 X 1,5 *6) | | | |
| | 4601 *8) | - | 1,3 | - | 26 | EEx me II T5/T6 *3) EEx md II T5/T6 *3) | -40 ... +80 (T5) -40 ... +70 (T6) | 1/2 NPT *6) | 0,85 | 9 | 7 |
| | 4603 *8) | - | 1,3 | - | 26 | IP66 T130°C | | M20 X 1,5 *6) | | | |
| | 3720 | 1,4 | - | 59 | - | XP (NEMA) *4) 4, 4X, 6, 6P, 7, 9 3 | -20 ... +60 | Flying leads 450 mm long | 0,4 | 10 | 1 |

Standard voltages 24 V DC, 230 V AC. other voltages on request. Design acc. to VDE 0580, EN 50014/50028.100% duty cycle.

*1) Catégorie II 2 GD, EC-Type-Examination-Certificate KEMA 02 ATEX 1347X

*2) Catégorie II 2 GD, EC-Type-Examination-Certificate KEMA 98 ATEX 4452 X

*3) Catégorie II 2 GD, EC-Type-Examination-Certificate PTB 02 ATEX 2085 X

*4) CSA-LR 57643-6, FM approved, for hazardous locations: Div. 1 and 2, Class I, II, III

*5) Required connector for DC: type 0570275. Valves can be operated with DC only.

For 230V AC application please use 200V DC coil, plus plug with rectifier

*6) Cable gland is not indicated in delivery

*7) IP65 according to DIN 40050/IEC 529 and DIN EN 600068-2-38

*8) This solenoid has a fuse with an appropriate rating.