




4K UHD 5MP AIO Camera UHD305LR3-F36M-D



5MP
MEGAPIXEL

FEATURES :

- ✓ Image Sensor : 1/2.5"
- ✓ Lens : 3.6mm Lens
- ✓ Resolution : 2560(H) x 1920(V) 5.0MP
- ✓ IR LEDES : 18 IR LED
- ✓ IR Distance : 30M
- ✓ OSD : Yes
- ✓ Min illumination : 0.5 Lux min. illumination
- ✓ Support : CVI, TVI, AHD & CVBS
- ✓ Protection : IP66 Weather Proof
- ✓ Power Input : DC 12V
- ✓ Power Consumption : 50mA (IR OFF) 250mA (IR ON)
- ✓ Mode change method _UTC control
- ✓ 94 x 94 x 67mm (L x W x H)



SENSOR



MIN. ILLUMINATION



DAY & NIGHT



AUTO WB



AGC



DWDR



WEATHER PROOF

DISTRIBUTE BY :



Design and specifications are subject to change without notice.



4K UHD 5MP AIO Camera

UHD305LR3-F36M-D



SPECIFICATION

Image Device	1/2.5"
Picture Elements	2560(H) x 1920(V) 5.0M
Lens	3.6mm Fixed
IR	18 IR LED
IR Distance	30 Meter
Frame Rate	5M/20FPS
Min.illumination	0.05 Lux / F1.2 , B/W : 0 Lux / F1.2 (With IR)
Signal Format	NTSC / PAL
Electronic Shutter	Auto : 1/25(30)~1/50,000
2D Noise Reduction	1~16 Adj (OSD Setting)
Digital WDR	On/Off
White Balance	ATW (default) MWB
Auto Gain Control	Auto
Day & Night Mode	External Control (default) Auto / Color / B/W
Video Setting	Contrast / Sharpness / Color Gain / DNR / DWDR
CDS Input Voltage	DC 1V~18V (Wide Voltage)
OSD Language	English / Simplified Chinese / Traditional Chinese
Video Output	AHD 5M / TVI 5M / CVI 4M / CVBS (6KV Lighting Protection)
Power Requirements	DC 12V (Wide Voltage 6~23V)
Power Consumption	50mA (IR OFF) 250mA (IR ON)
Operating Temp	-10°C ~ +50°C (14°F ~ 122 °F)
Storage Temp	-40°C ~ +60°C (40°F ~ 140 °F)
Dimension	94 x 94 x 67mm (L x W x H)

