



## Hose reel HR 25

Hose reel HR 25 with rust-resistant frame. Includes wall bracket, 15 m 1/2" PrimoFlex® hose, spray nozzle, four Plus universal hose connectors, 3/4" thread tap connector. Ready to use.



**1** With wall bracket, locating screws, 15 m 1/2" PrimoFlex® hose, sprayer, 4 Universal hose connectors Plus (3 x 2.645-003.0, 1 x 2.645-004.0) and 3/4 tap adaptor.

■ Ready to use

**2** Compact dimensions

■ Can be easily stored

**3** Powder-coated steel frame for mobile and stationary use

■ Robust and corrosion-free.



## Hose reel HR 25

- Robust stainless frame of powder-coated steel for mobile and stationary use
- Compact dimensions
- With wall bracket, locating screws, 15 m 1/2 PrimoFlex® hose, nozzle, 4 Universal hose connectors Plus (3x 2.645-003.0, 1x 2.645-004) and 3/4 tap adaptor.
- Fully assembled

### Technical data

<b>Order no.</b>	2.645-041.0	
<b>EAN code</b>	4039784289239	
<b>Hose capacity</b>	<b>m</b>	max. 15 (1/2") /
<b>Bursting pressure</b>	<b>bar</b>	24
<b>Weight</b>	<b>kg</b>	2.84
<b>Weight incl. packaging</b>	<b>kg</b>	3.45
<b>Dimensions (L × W × H)</b>	<b>mm</b>	265 × 300 × 305

-- When connecting these products to the drinking water network, you must observe the requirements of EN 1717. If necessary, ask your sanitary specialist.

### Equipment

<b>Cone jet</b>	■
<b>Spray mist</b>	-
<b>Horizontal flat jet</b>	-
<b>Aerator jet</b>	-
<b>Point jet</b>	■
<b>Sprinkler</b>	-
<b>Vertical flat jet</b>	-

When connecting these products to the drinking water network, you must observe the requirements of EN 1717. If necessary, ask your sanitary specialist.