




## Oscillating sprinkler OS 5.320 S

Oscillating sprinkler OS 5.320 S for watering medium-sized and large areas and gardens. Adjustable flow control (0-max.). Covers up to 320 m2.







- 1 Continuous reach adjustment
- Precise watering.

- 3 Adjustable width of spray
- Different spray angles for targeted watering.
- 2 Loop for hanging the device integrated into the handle
- For simple storage/hanging.

- 4 Splash guard
- Convenient alignment

## **TECHNICAL DATA AND EQUIPMENT**





## Oscillating sprinkler OS 5.320 S

- With splash guard for convenient alignment of the sprinkler without needing to get wet
- Continuous adjustment of the water volume (0-max.)
- Floor fixing
- Suspension brackets for secure storage
- Dirt-resistant, long-lasting gear
- Max. watering area (for 4 bar system pressure): 320 m

Technical data		
Order no.		2.645-134.0
EAN code		4039784426344
Sprinkling area (2 bar)		60 - 190 m² (2 bar)
Sprinkling area (4 bar)		100 - 320 m² (4 bar)
Width of spray (2 bar)	m	12
Width of spray (4 bar)	m	16
Area coverage (2 bar)	m	5 / 16
Area coverage (4 bar)	m	6 / 20
Weight	kg	0.78
Weight incl. packaging	kg	0.9
Dimensions (L × W × H)	mm	546 × 160 × 88

## OSCILLATING SPRINKLER OS 5.320 S 2.645-134.0











		Order no.			Price	Description
		Order no.			FIICE	Description
<b>Hoses</b> PrimoFlex Plus hose 1/2" - 20 m	1	2.645-144.0				20 m PrimoFlex* Plus quality garden hose (1/2*). With pressure-resistant reinforcement mesh. Contains no substances that are harmful to health. Bursting pressure: 45 bar. High temperature resistance from -20 to 65 °C.
Hose connection systems						
Universal hose coupling Plus	2	2.645-193.0				Universal hose coupling plus with soft plastic recessed grips for comfortable handling. Compatible with all click systems.
Universal hose coupling Plus with Aqua Stop	3	2.645-194.0				Universal hose coupling plus with Aqua Stop and soft plastic recessed grips for comfortable handling. Compatible with all click systems.
G3/4 tap adaptor with G1/2 reduc- er	4	2.645-006.0				Extremely tough tap connector 3/4" thread with 1/2" thread reducer. The reducer allows connection to two thread sizes. Compatible with all click systems.

<sup>☐</sup> Available accessories.