



HD 13/35-4 Cage

This product uses up to 350 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



1 High-performance crankshaft pump

- Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.

2 Safe storage

- Accessories and tools are stored in a protected compartment. This means that everything is always in its place.



HD 13/35-4 Cage

- Robust industrial gun
- Dry run protection (optional)

Technical data

Order no.	1.367-154.0	
EAN code	4039784730984	
Working pressure	bar / MPa	100 – max. 350 / 10 – max. 35
Flow rate	l/h	500 – 1300
Inlet temperature	°C	max. 60
Fuel	Electric	
Engine rating	kW	15
Current type	Ph / V / Hz	3 / 400 / 50
Pump type	Maximum performance Kärcher crankshaft pump	
Weight without accessories	kg	160
Weight (with accessories)	kg	195
Dimensions (L × W × H)	mm	930 × 800 × 920

Equipment

Electro start	–	
High-pressure hose	m	10 / Heavy duty
Spray gun	Industrial trigger gun	
Stainless steel spray lance	mm	700
Flat jet nozzle	■	
Safety valve	■	
Elapsed time counter	■	

■ Included in the scope of supply.

HD 13/35-4 CAGE

1.367-154.0

KÄRCHER


		Order no.	Length				Price	Description	
High-pressure hoses									
Pressure hose	1	6.391-846.0						650 bar, M 22 x 1.5	■
	2	6.391-856.0						650 bar, M 22 x 1.5.	□
	3	6.391-848.0						650 bar, M 22 x 1.5	□
	4	6.391-857.0						650 bar, M 22 x 1.5.	□
	5	6.391-847.0							□
	6	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	□
Trigger guns									
Kärcher industry gun	7	4.775-824.0						650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
Spray lances									
Spray lance	8	4.760-679.0						With nozzle holder.	■
	9	4.760-653.0							□
Jet pipe complete 1550 mm 65 MPa	10	4.760-675.3							□
Spray lance	11	4.760-677.0							□
Spray lance extension	12	4.760-699.0						Spray lance extension 800 mm, 65 MPa.	□
Power nozzles									
Flat jet nozzle	13	5.765-166.0						15° flat jet nozzle 15049 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (electr.).	■
Point jet nozzle	14	5.765-162.0						Point jet nozzle 0049 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h. (electr.).	□
Attachment kits									
ABS protection against dry run	15	2.641-922.0						For electric motors.	□
ABS protection against water shortage	16	2.851-028.0						ABS steering rollers.	□
Couplings and connectors									
Coupling	17	4.403-004.0						For joining and extending HD hoses. Connection 2 x M 22 x 1.5. Material: Stainless steel.	□
Grease for stainless steel threaded joints	18	6.280-180.0						Grease for stainless steel screw connections.	□
Single-jet rotary nozzles									
Tool for changing rotor seat	19	6.025-233.0						For F3, F4, F1, F25.	□
Rotary jet	20	4.767-173.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, brass.	□
Power rotary jet F7	21	6.415-085.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
Repair set Power Rotary Jet F9 050	22	6.812-003.0						Suitable for up to 350 bar pressure and water volume of 1300 litres/hour: repair set, comprising rotor, fitting and O-ring for Power Rotary Jet.	□
Power rotary jet F7	23	6.415-914.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
Power rotary jet repair kit F7	24	6.025-436.0						Repair kit for power rotary jet, order no. 6.415-914.0. Suitable for 350 bar working pressure and 1,300 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	□
Screw nozzles F21									
Dummy nozzle F21	25	6.025-237.0						F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	□

■ Included in the scope of supply. □ Available accessories.

HD 13/35-4 CAGE

1.367-154.0

KÄRCHER


		Order no.	Length					Price	Description	
Round jet nozzle F21, Saphir	26	9.886-216.0							Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Pipe cleaning										
Foot valve for pipe cleaning	27	6.470-223.0							Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle standard 050 50MPa	28	4.765-012.0							Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning nozzle Four 050 50MPa	29	4.765-016.0							For pipe cleaning hoses with G1/4" threaded connection: Quattro pipe cleaning nozzle. Nozzle configuration: 3x backward and 1x forward.	<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	30	5.763-092.0							For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning hose	31	6.392-401.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	32	6.392-402.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	33	6.392-403.0							For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
Surface cleaner										
Surface Cleaner FRI 50 Me	34	2.643-577.0							Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle package 025 FRI 50 Me	35	6.415-045.0							Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 025.	<input type="checkbox"/>
Abrasive blaster										
Required adapter for abrasive blasters	36	5.401-325.0							M 20 x 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Abrasive blaster, incl. 3 x 0.7 nozzle	37	9.872-435.0							Abrasive spray head with nozzle size 3 x 0.7 mm for wet sand blasting. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	38	6.025-346.0							Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>
F98 nozzle kit, D 0.70 mm	39	9.886-551.0							For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	<input type="checkbox"/>
F98 nozzle for abrasive blaster	40	6.025-255.0							Nozzle (nozzle size 0.7 mm) for abrasive spray head for wet sand blasting.	<input type="checkbox"/>
Suction lance	41	6.025-258.0							For the suction of spray agents.	<input type="checkbox"/>
Abrasive material hose	42	6.025-308.0							Abrasive hose.	<input type="checkbox"/>
Mounting tool for nozzle set	43	6.025-257.0							For F98 nozzles.	<input type="checkbox"/>
Abrasive	44	6.025-309.0							25 kg, 0.5-1.00 mm, garnet sand.	<input type="checkbox"/>
	45	6.025-310.0							25 kg, 0.7-1.40 mm, garnet sand.	<input type="checkbox"/>
Multi-jet rotary nozzles										
Nozzle body	46	9.917-677.0							Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	<input type="checkbox"/>
Nozzle carrier head TD09	47	9.899-828.0							6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.