




HD 13/35 Ge Cage

This product uses up to 350 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



1 Speed regulation

- The speed is automatically reduced in standby mode. This protects the engine and saves energy.



2 Portability



3 Independence



HD 13/35 Ge Cage

- Robust industrial gun
- Dry run protection (optional)
- Speed regulation

Technical data

Order no.	1.367-505.0	
EAN code	4039784731004	
Working pressure	bar / MPa	100 – max. 350 / 10 – 35
Flow rate	l/h	500 – 1300
Inlet temperature	°C	max. 60
Fuel	Petrol	
Motor manufacturer	Honda	
Motor type	GX 690	
Engine rating	kW	16
Pump type	Maximum performance Kärcher crankshaft pump	
Weight without accessories	kg	122
Weight (with accessories)	kg	150
Dimensions (L × W × H)	mm	930 × 800 × 920

Equipment

Electro start	■	
High-pressure hose	m	10 / Heavy duty
Spray gun	Industrial trigger gun	
Stainless steel spray lance	mm	700
Flat jet nozzle	■	
Safety valve	■	
Elapsed time counter	■	

■ Included in the scope of supply.

HD 13/35 GE CAGE

1.367-505.0

KÄRCHER


		Order no.	Length				Price	Description	
High-pressure hoses									
Pressure hose	1	6.391-846.0						650 bar, M 22 x 1.5	■
	2	6.391-856.0						650 bar, M 22 x 1.5.	□
	3	6.391-848.0						650 bar, M 22 x 1.5	□
	4	6.391-857.0						650 bar, M 22 x 1.5.	□
	5	6.391-847.0							□
	6	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	□
Trigger guns									
Kärcher industry gun	7	4.775-824.0						650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
Spray lances									
Spray lance	8	4.760-679.0						With nozzle holder.	■
	9	4.760-653.0							□
Jet pipe complete 1550 mm 65 MPa	10	4.760-675.3							□
Spray lance	11	4.760-677.0							□
Spray lance extension	12	4.760-699.0						Spray lance extension 800 mm, 65 MPa.	□
Power nozzles									
Flat jet nozzle	13	5.765-165.0						15° flat jet nozzle 15046 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (petrol, 60 Hz).	■
Point jet nozzle	14	5.765-161.0						Point jet nozzle 0046 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (petrol, 60 Hz).	□
Attachment kits									
Attachment kit water shortage protection	15	2.641-923.0						For petrol engines.	□
ABS protection against water shortage	16	2.851-028.0						ABS steering rollers.	□
Couplings and connectors									
Coupling	17	4.403-004.0						For joining and extending HD hoses. Connection 2 x M 22 x 1.5. Material: Stainless steel.	□
Grease for stainless steel threaded joints	18	6.280-180.0						Grease for stainless steel screw connections.	□
Single-jet rotary nozzles									
Tool for changing rotor seat	19	6.025-233.0						For F3, F4, F1, F25.	□
Rotary jet	20	4.767-173.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, brass.	□
Power rotary jet F7	21	6.415-085.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
Repair set Power Rotary Jet F9 050	22	6.812-003.0						Suitable for up to 350 bar pressure and water volume of 1300 litres/hour: repair set, comprising rotor, fitting and O-ring for Power Rotary Jet.	□
Power rotary jet F7	23	6.415-914.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
Power rotary jet repair kit F7	24	6.025-436.0						Repair kit for power rotary jet, order no. 6.415-914.0. Suitable for 350 bar working pressure and 1,300 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	□

■ Included in the scope of supply. □ Available accessories.

HD 13/35 GE CAGE

1.367-505.0

KÄRCHER



Page 1

0.Object

page6152306025218

std_01_272x272px.jpg

wurde anstatt

PAGE6152306391

std_1_272x272px.JPG

plaziert. 6 31-33

1.Object

page6152309886214

std_1_272x272px.jpg

wurde anstatt

PAGE6152304775823

std_1_272x272px.JPG

plaziert. 6 40

2.Object

page6152306470223

std_01_272x272px.jpg

wurde anstatt

		Order no.	Length				Price	Description	
Screw nozzles F21									
Dummy nozzle F21	25	6.025-237.0						F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir	26	9.886-216.0						Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Pipe cleaning									
Foot valve for pipe cleaning	27	6.470-223.0						Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle standard 050 50MPa	28	4.765-012.0						Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x back-ward.	<input type="checkbox"/>
Pipe cleaning nozzle Four 050 50MPa	29	4.765-016.0						For pipe cleaning hoses with G1/4" threaded connection: Quattro pipe cleaning nozzle. Nozzle configuration: 3x back-ward and 1x forward.	<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	30	5.763-092.0						For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x back-ward.	<input type="checkbox"/>
Pipe cleaning hose	31	6.392-401.0						Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	32	6.392-402.0						Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	33	6.392-403.0						For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
Surface cleaner									
Surface Cleaner FRI 50 Me	34	2.643-577.0						Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle package 025 FRI 50 Me	35	6.415-045.0						Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 025.	<input type="checkbox"/>
Abrasive blaster									
Required adapter for abrasive blasters	36	5.401-325.0						M 20 x 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Abrasive blaster, incl. 3 x 0.7 nozzle	37	9.872-435.0						Abrasive spray head with nozzle size 3 x 0.7 mm for wet sand blasting. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	38	6.025-346.0						Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>
F98 nozzle kit, D 0.70 mm	39	9.886-551.0						For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	<input type="checkbox"/>
F98 nozzle for abrasive blaster	40	6.025-255.0						Nozzle (nozzle size 0.7 mm) for abrasive spray head for wet sand blasting.	<input type="checkbox"/>
Suction lance	41	6.025-258.0						For the suction of spray agents.	<input type="checkbox"/>
Abrasive material hose	42	6.025-308.0						Abrasive hose.	<input type="checkbox"/>
Mounting tool for nozzle set	43	6.025-257.0						For F98 nozzles.	<input type="checkbox"/>
Abrasive	44	6.025-309.0						25 kg, 0.5-1.00 mm, garnet sand.	<input type="checkbox"/>
	45	6.025-310.0						25 kg, 0.7-1.40 mm, garnet sand.	<input type="checkbox"/>
Multi-jet rotary nozzles									
Nozzle body	46	9.917-677.0						Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	<input type="checkbox"/>
Nozzle carrier head TD09	47	9.899-828.0						6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.