



HD 9/50 Ge Cage

This product uses up to 500 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



4-6 h



FLAT FREE TIRES



E-Start

1 Industrial spray gun

- Robust and durable: The new Kärcher industrial trigger gun was designed specially for heavy-duty use.

2 Speed regulation

- The speed is automatically reduced in standby mode. This protects the engine and saves energy.



HD 9/50 Ge Cage

- Robust industrial gun
- Dry run protection (optional)
- Speed regulation

Technical data

Order no.	1.367-506.0	
EAN code	4039784731035	
Working pressure	bar / MPa	150 – max. 500 / 15 – max. 50
Flow rate	l/h	500 – 900
Inlet temperature	°C	max. 60
Fuel	Petrol	
Motor manufacturer	Honda	
Motor type	GX 690	
Engine rating	kW	16
Pump type	Maximum performance Kärcher crankshaft pump	
Weight without accessories	kg	122
Weight (with accessories)	kg	150
Dimensions (L × W × H)	mm	930 × 800 × 920

Equipment

Electro start	■	
High-pressure hose	m	10 / Heavy duty
Spray gun	Industrial trigger gun	
Stainless steel spray lance	mm	700
Flat jet nozzle	■	
Safety valve	■	
Elapsed time counter	■	

■ Included in the scope of supply.

HD 9/50 GE CAGE

1.367-506.0

KÄRCHER



		Order no.	Length			Price	Description	
High-pressure hoses								
Pressure hose	1	6.391-848.0					650 bar, M 22 x 1.5	<input checked="" type="checkbox"/>
	2	6.391-856.0					650 bar, M 22 x 1.5.	<input type="checkbox"/>
	3	6.391-857.0						<input type="checkbox"/>
	4	6.391-020.0					Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 640 bar working pressure.	<input type="checkbox"/>
	5	6.391-846.0					650 bar, M 22 x 1.5	<input type="checkbox"/>
	6	6.391-847.0					650 bar, M 22 x 1.5.	<input type="checkbox"/>
	7	6.391-019.0					Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	<input type="checkbox"/>
Trigger guns								
Kärcher industry gun	8	4.775-824.0					650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	<input checked="" type="checkbox"/>
Spray lances								
Spray lance	9	4.760-679.0					With nozzle holder.	<input checked="" type="checkbox"/>
	10	4.760-653.0						<input type="checkbox"/>
Jet pipe complete 1550 mm 65 MPa	11	4.760-675.3						<input type="checkbox"/>
Spray lance	12	4.760-677.0						<input type="checkbox"/>
Spray lance extension	13	4.760-699.0					Spray lance extension 800 mm, 65 MPa.	<input type="checkbox"/>
Power nozzles								
Flat jet nozzle	14	5.765-163.0					15° flat jet nozzle 15028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	<input checked="" type="checkbox"/>
Point jet nozzle	15	5.765-160.0					Point jet nozzle 0028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	<input type="checkbox"/>
Attachment kits								
Attachment kit water shortage protection	16	2.641-923.0					For petrol engines.	<input type="checkbox"/>
ABS protection against water shortage	17	2.851-028.0					ABS steering rollers.	<input type="checkbox"/>
Couplings and connectors								
Coupling	18	4.403-004.0					For joining and extending HD hoses. Connection 2 x M 22 x 1.5. Material: Stainless steel.	<input type="checkbox"/>
Grease for stainless steel threaded joints	19	6.280-180.0					Grease for stainless steel screw connections.	<input type="checkbox"/>
Single-jet rotary nozzles								
Tool for changing rotor seat	20	6.025-233.0					For F3, F4, F1, F25.	<input type="checkbox"/>
Power Rotary Jet F8 030	21	6.415-069.0					500 bar, 1.05 mm, 900 l/h, M 20 x 1, stainless steel.	<input type="checkbox"/>
Repair set Power Rotary Jet F8 030	22	6.812-000.0					Repair set for Power Rotary Jet. Suitable for up to 500 bar pressure and water volume of 900 litres/hour. Incl. rotor, fitting and O-ring.	<input type="checkbox"/>
Power rotary jet repair kit F8	23	6.025-437.0					Repair kit for power rotary jet, order no. 6.415-915.0. Suitable for 500 bar pressure and 900 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.

