

# Spray Gun **NEW-71**

## NEW-71 漆枪结构解析图



**esko**

Spray air pressure adjustment knob

Air interface

# esiko

High precision industrial drilling machine



Model / 型號	EK-13A	EK-16A	EK-20A	EK-25A
Max Drilling Diameter(mm)	Φ13mm(1/2")	Φ16mm(5/8")	Φ20mm(3/4")	Φ25mm(1")
Motor Power	350W	750W	750W	1500W
Spindle Travel(mm)	50	85	85	120
Class Of Speed	5	16	16	12
Speed 50Hz	620-2620 R.P.M.	180-2770 R.P.M.	180-2770 R.P.M.	150-2450 R.P.M.
Spindle Taper	B16	MT2	MT2	MT3
Max. distance from spindle axis to surface of column(mm)	105	162.5	180	225
Max. distance from spindle end to surface of table(mm)	220	450	585	765
Max. distance from spindle end to surface of base(mm)	300	630	805	1225
Swing(mm)	210	325	360	450
Table Size(mm)	160X160	Φ290	290X290	350X350
Base Size(mm)	290X190	420X250	460X272	470X360
Column Diameter(mm)	Φ46	Φ72	Φ72	Φ92
Height(mm)	580	980	1200	1710
Net Weight/Gross Weight(kg)	19/20	50/52	63/66	120/128



## TRANSMISSION JACK ENGINE STAND / CRANE



### EK-TJ0501 TRANSMISSION JACK 0.5 TON

#### FEATURES

Capacity	0.5 Ton
Min Height	1140mm
Max Height	1965mm
Nw	31kgs
Gw	35kgs
Package Size	1120 x 300 x 280mm



### EK-ES125 ENGINE STAND 1250 LBS

#### FEATURES

Capacity	1250 lbs
Product Size	995 x 705 x 960mm
Nw	27.5kgs
Gw	29.2kgs



### EK-EC2T 2 TON ENGINE CRANE

#### FEATURES

Capacity	2 Ton
Lifting Range	25-2446mm
Length	1740mm
Width	1040mm
Height	1550mm
Package Size	1# 27.5kgs / 29 kgs 2# 73.78kgs / 75.92kgs



### EK-ES150 ENGINE STAND 1500 LBS

#### FEATURES

Capacity	1500 lbs
Product Size	875 x 820 x 860mm
Nw	33.5kgs
Gw	35.3kgs
Package Size	860 x 420 x 165mm



### EK-3PT / EK-5PT HAND PALLET TRUCK



3 TON / 5 TON



- One Piece Cast Pump with Reliable Oil-proof Hydraulic System



- Polyurethane Wheels

#### FEATURES

Capacity	3 TON / 5 TON
H Min. Fork Height	83MM / 100MM
H Max. Fork Height	195MM / 210MM
Steering Wheel	Ø 180 X 50MM / 180 X 60MM
Load Roller	Ø 80 X 68 / 88 X 106
Fork Width	685MM / 700MM
Fork Length	1220MM / 1310MM
Weight	95KG / 200KG

\* Whole casting pump with 35mm piston rod

# HYDRAULIC SERVICE JACK

# esko

## EK-J3075L

- Extra Low Profile Design
- Hydraulic Oil By-pass System Protects Ram from being Over-extended
- "Quick Start" Double Pump Technology for Fast Operation to Contact Point

### FEATURES

Capacity	3 Ton	N.W	31.4kgs
Min Height	75mm	G.W	3.2 Kgs
Max Height	505mm	Package size	805 x 370 x 205mm
Product Size	740 x 360 x 160mm		

## EK-J30D

### FEATURES

Capacity	3 Ton	N.W	30.7kgs
Min Height	133mm	G.W	33 Kgs
Max Height	465mm	Package size	740 x 380 x 200mm
Product Size	682 x 344 x 155mm		

## EK-J30/30S

### FEATURES

Capacity	3 Ton	N.W	28.2kgs
Min Height	130mm	G.W	29.7 Kgs
Max Height	465mm	Package size	615 x 375 x 200mm
Product Size	572 x 328 x 175mm		

## Ratchet Style Jack Stands

### FEATURES

Capacity	3 Ton	Product Size	193 x 180mm
Min Height	276mm	G.W	5.5 Kgs
Max Height	435mm	Package size	210 x 190 x 350mm



## IMPACT WRENCH

- Twin hammer impact wrench
- Heavy duty for professional uses such as automotive, light truck, industrial, tire shop
- The pneumatic motor with high effect designed, low consumption and high torque output
- Spherical iron cylinder with heat treatment and high hardness, durable and long lifespan, torque and output steadily
- High strength hammer mechanism
- Two-piece construction for easy maintain

### EA-4625

TWIN HAMMER / HANDLE EXHAUST



#### FEATURES

Square Drive (Inch)	1/2"	Air Inlet (PT)	1/4"
Capacity Bolt Size	inch 0.71 mm 18	Air Hose (I.D.)	3/8"
Free Speed (r.p.m)	7000	Net Weight	Lbs 6.28 Kgs 2.84
Max. Torque	ft-lb 625 N.m 850	Packing Pcs/Ctrv/Cuft'	8pcs/ctrv/1.19'
Overall Length	inch 7.48 mm 190		

### EA-1902

TWIN HAMMER / HANDLE EXHAUST



#### FEATURES

Square Drive (Inch)	3/4" 1"	Air Inlet (PT)	1/2"
Capacity Bolt Size	inch 1.40 mm 36	Air Hose (I.D.)	1/2"
Free Speed (r.p.m)	4300	Net Weight	Lbs 17.60 Kgs 8.00
Max. Torque	ft-lb 1540 N.m 2000	Packing Pcs/Ctrv/Cuft'	2pcs/ctrv/1.84'
Overall Length	inch 9.40 mm 240		

### EA-2502

PINLESS HAMMER MECHANISM



#### FEATURES

Square Drive (Inch)	1"	Air Inlet (PT)	1/2"
Capacity Bolt Size	inch 1.77 mm 46	Air Hose (I.D.)	1/2"
Free Speed (r.p.m)	3500	Net Weight	Lbs 36.60 Kgs 16.56
Max. Torque	ft-lb 2353 N.m 3200	Packing Pcs/Ctrv/Cuft'	2pcs/ctrv/2.18'
Overall Length	inch 24.21 mm 615		