

- Floor Type Electrode Oven designed for **Re-Baking**, **Re-Conditioning** and **Holding** of welding electrode for high quality weld with build in adjustable thermostat controlled with digital temperature display.
- **PID MICRO-PROCESSOR POWER CONTROLLER** for better temperature accuracy.
- Energy saving design ovens used high temperature door gasket to prevent heat loss.

MILD STEEL BODY
E 060M / E 120M



STAINLESS STEEL BODY
E 060S / E 120S



Model	E 060M / E 060S	E 120M / E 120S
Capacity (Rod Lght. 450mm)	60 kgs (+/-)	120 kgs (+/-)
Temperature Range (Average Stabilized)	30°C ~ 400°C (86°F ~ 752°F)	30°C ~ 400°C (86°F ~ 752°F)
Input Voltage 50/60Hz	1ph, 220-240VAC	1ph, 220-240VAC
Input Power	900W	1800W
External Dimension (mm)	620 x 735 x 436	790 x 735 x 436
Internal Dimension (mm)	210 x 500 x 280	375 x 500 x 280
Body Insulation (Ceramic wool)	75mm	75mm
Weight	45 kgs	57 kgs
Applications	Welding Electrodes	



STAINLESS STEEL BODY
E 200S / E 300S
E 400S / E 600S



MILD STEEL BODY
E 200M / E 300M
E 400M / E 600M
E 1000M



TIMER Option: (0-10hr)

Timer changeover baking temperature to holding temperature controller continuously when time expires. This option saves energy and reduces oxidation to electrode. Holding temperature range from 0 to 200°C.

Model	E 200M / E 200S	E 300M / E 300S	E 400M / E 400S	E 600M / E 600S	E 1000M
Capacity (Rod Lght. 450mm)	210 kgs (+/-)	300 kgs (+/-)	400 kgs (+/-)	600 kgs (+/-)	1000 kgs (+/-)
Temperature Range (Average stabilized)	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F
Input Voltage 50/60Hz	1ph, 220-240VAC 3ph, 380-440VAC	1ph, 220-240VAC 3ph, 380-440VAC	3ph, 380-440 VAC	3ph, 380-440 VAC	3ph, 380-440 VAC
Input Power+/-	2700W / 1900W	2700W / 1900W	5300W	6600W	7900W
External Dimension (mm)	960 x 735 x 620	1115 x 735 x 620	1140 x 755 x 905	1440 x 787 x 910	1700 x 787 x 1060
Internal Dimension (mm)	505 x 500 x 455	650 x 500 x 455	650 x 500 x 695	950 x 500 x 695	1200 x 500 x 810
Body Insulation (Ceramic wool)	75mm	75mm	100 mm	100mm	100mm
Weight	86 kgs	96 kgs	168 kgs	217 kgs	242 kgs
Applications	Welding Electrodes				