



DVOIL MOULD EX

HIGH PERFORMANCE MOULD RELEASE AGENT

DESCRIPTION

DVOIL MOULD EX is a chemical release agent for both timber and steel formworks. It is blended with high efficient releasing properties agent to function as a bond breaker between formwork and fresh concrete.

ADVANTAGES

- Stain free on concrete.
- Provides protection to both timber and steel formworks as it acts as a rust inhibitor and water proofer.
- Ready to use and should not be diluted.
- Usable for all types of formworks.

INSTRUTIONS FOR USE SURFACE

The surfaces to be coated with **DVOIL MOULD EX** must be clean and free from dirt, old concrete or greases.

APPLICATION

Use brush, sponge or spray equipment to apply on the formwork surface. Any excess liquid remaining on the surface after application should be mopped off. Allow 1-3 hours to dry before pouring concrete. If the concrete pouring delayed more than 48 hours, the surface should be recoated.

COVERAGE

DVOIL MOULD EX should be applied at the following stated coverage rates to obtain a thin and even film over the entire surface of the formwork:

- Timber formwork : 1 liter per 20m²
- Metal formwork : 1 liter per 31m²

SAFETY

Wear gloves and goggles during application. If in contact with skin, wash thoroughly with soap and water. If in contact with eyes or mucous membrane, flush immediately with plenty of water and seek medical attention without delay. Use with adequate ventilation.

Technical Data (typical values)	DVOIL MOULD EX
Appearance, Visual	Brown Yellowish
Chemical Type	Oil Based
Density at 25 °C	0.90

*The content of this data sheet given in good faith but without warranty