

ATF FLUSH

Spanjaard ATF Flush is formulated with a special blend of additives to clean and prepare automatic transmissions for new fluid.

APPLICATION

- Compatible with all automatic transmission fluids (ATF).
- Removes sludge and varnish deposits.
- Ensures optimum performance of the new fluid.
- Safe on all seals and contains no harmful solvents.

Note: Only for use in Automatic Transmissions. Not suitable for use with continuously variable transmissions (CVT) or dual clutch transmissions (DCT).



APPLICATION INSTRUCTIONS

Drain 250ml of the old fluid.

Add full contents of the ATF Flush tin (250ml) directly to transmission.

Drive vehicle at low speed for 30 minutes to fully circulate the flush fluid.

Drain transmission completely and refill with ATF according to vehicle manufacturer's specifications.

For best results it is recommended that the automatic transmission filter is also replaced after flushing.

TYPICAL PROPERTIES

Colour	Clear yellow liquid
Density, (25°C), g/ml	0,87
Viscosity (40°C),cSt	8-10

HANDLING AND STORAGE

DANGER - May be fatal if swallowed and enters airway. If swallowed immediately call a poison centre or doctor. Keep out of reach of children.

PACKAGING

250ml tin

CP/mg/ATF Flush – May 2016