



TEXFOOD MP 1

HIGH PERFORMANCE FOOD GRADE GREASE UP TO 150°C



Nonfood Compounds
(Category Code H1)



DESCRIPTION

LUBTEX® TEXFOOD MP 1 is aluminium complex thickened lubricating grease based on pharmaceutical white oils. The grease contains antioxidants and EP/AW additives. The thickener, together with the special base oil, makes the product suitable for lubrication in applications where there is the possibility of incidental or accidental food contact.

LUBTEX® TEXFOOD MP 1 is high performance universal food machinery grease. The product's all-round properties make it suitable for various types of bearing applications including heavy load conditions.

OUTSTANDING FEATURES

- Good oxidation stability
- Excellent load carrying capacity
- Suitable for food machinery

DIRECTION FOR USE

LUBTEX® TEXFOOD MP 1 can be applied manually, or by using a standard grease gun, or via a central lubricating system designed for and capable of pumping an NLGI No.1 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary, purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and always apply the quantity of grease recommended by the bearing manufacturer.

Technical Data (typical value)	TEXFOOD MP 1
Thickener	Aluminium complex
Base oil	Semi-synthetic base oil
NLGI Grade	1
Dropping point	>230°C
Base oil viscosity at 40°C 100°C	220 mm²/s 20 mm²/s
4-ball weld load	400kg
Operating Temperature Range °C	- 20 to 150°C

*The content of this data sheet given in good faith but without warranty