


Floor Ceiling Convertible Deluxe – R410A



Features



Smart Convertible

Indoor unit can be installed on floor or ceiling with a dual drain pan.



4-Speed Drive

4-Speed Drive provides extra cooling during the hotter days.



Rapid Cooling

Achieve faster cooling with our true speed fan design.



Super Slim

(Applicable to 10,200~13,700 Btu/hr)
Super slim design that fits narrow ceiling spaces.



Easy Maintenance

Air filter is easily dismantled and cleaned, which allow a healthy indoor environment.



Other Features



Comfortable Sleep




Auto Mode



24 Hour Timer



High Performance Compressor




Auto Swing



Exquisite Filter



3 Minutes Protection



Auto Restart



Self - Diagnosis

Specifications

Indoor Unit



Outdoor Unit



Wireless Remote Controller



Wired Remote Controller (Optional)



Indoor Model	Wireless	YCE3F10AAS-W	YCE3F15AAS-W	YCE3F20AAS-W	YCE3F25AAS-W	
	Wired	YCE3F10AAS-SLM	YCE3F15AAS-SLM	YCE3F20AAS-SLM	YCE3F25AAS-SLM	
Outdoor Model		YSM3F10AAS	YSM3F15AAS	YSM3F20AAS	YSM3F25AAS	
Cooling Capacity	Btu/hr	10,200	13,500	18,800	26,100	
Input Power	W	840	1,120	1,820	2,370	
Rated Current	A	3.65	4.87	7.91	10.30	
EER	Btu/hr/W	12.14	12.05	10.33	11.01	
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz				
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE				
Indoor Air Flow (H/L)	CFM	324/247	390/265	534/380	883/738	
Noise Level (H/L)	dB(A)	46/32	46/36	47/36	47/42	
Dimension (WxDxH)	Indoor	mm	990x665x199	990x665x199	990x655x199	1,298x700x240
	Outdoor	mm	780x245x540	780x260x680	810x340x680	810x340x680
Unit Weight	Indoor	kg	31.00	31.00	31.00	39.00
	Outdoor	kg	36.00	42.00	49.00	63.00
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4	6.35 / 1/4	9.52 / 3/8
	Gas	mm/in	12.70 / 1/2	12.70 / 1/2	15.88 / 5/8	15.88 / 5/8

Indoor Model	Wireless	YCE3F30AAS-W	YCE3F35AAS-W	YCE3F40AAS-W	YCE3F50AAS-W	
	Wired	YCE3F30AAS-SLM	YCE3F35AAS-SLM	YCE3F40AAS-SLM	YCE3F50AAS-SLM	
Outdoor Model		YSM3F30AAS	YSM3F35AAS	YSM3F40AAS	YSM3F50AAS	
Cooling Capacity	Btu/hr	30,500	34,500	41,000	50,000	
Input Power	W	2,750	2,950	3,600	4,450	
Rated Current	A	11.96	12.83	6.80	8.30	
EER	Btu/hr/W	11.09	11.69	11.39	11.24	
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz		3Ph/380-415V/50Hz		
Refrigerant Type/ Control		R410A / INDOOR CAP.TUBE				
Indoor Air Flow (H/L)	CFM	1,031/794	1,031/794	1,151/832	1,151/832	
Noise Level (H/L)	dB(A)	48/44	48/44	51/44	51/44	
Dimension (WxDxH)	Indoor	mm	1,298x700x240	1,298x700x240	1,570x700x240	1,570x700x240
	Outdoor	mm	862x375x730	840x415x960	1,008x410x830	1,008x410x830
Unit Weight	Indoor	kg	39.00	39.00	54.00	54.00
	Outdoor	kg	72.00	84.00	93.00	97.00
Refrigerant Piping	Liquid	mm/in	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8
	Gas	mm/in	15.88 / 5/8	15.88 / 5/8	19.05 / 3/4	19.05 / 3/4

Note:

- All designs and specifications are subjected to change without prior notice for product improvement
- Nominal cooling capacity is based on the conditions below
Power supply, 1Ph/230V/50Hz or 3Ph/380V/50Hz
Cooling - Indoor: 27°C DB /19°C WB and Outdoor 35°C DB / 24°C WB
- Units are tested and comply with the latest ISO5151

Head Office:

YORK (MALAYSIA) SALES & SERVICE SDN BHD (168496-T)

Bangunan THK, Suite 2.1, 2nd Floor,
No.2A, Jalan 243, Section 51A,
46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel. 03-7628 4100 Fax: 03-7628 4101

Branches:

Penang Branch

Tel. 04-397 0213 Fax: 04-397 2045

Melaka Branch

Tel. 06-283 3188 Fax: 06 -283 3188

Johor Bahru Branch

Tel. 07-354 9878 Fax: 07-354 9871

Kuching

Tel. 082-553 100 Fax: 082-553 200

Kota Kinabalu Branch

Tel. 088-448 350 Fax: 088-448 352



(Applicable to 2.8 HP and below)

Authorized Dealer

Customer Care Centre: 1800 - 88 - YORK (9675)

Website: www.york.com/my