






| BAR CODE ITEM PART NO | PRODUCT PHOTO | DESCRIPTION & SPECIFICATION |
|--------------------------|------------------|--------------------------------|
|--------------------------|------------------|--------------------------------|



ITALIAN CS12A COMPRESSOR PRESSURE SWITCH (12 BAR) C/W UNLOADER VALVE.

| | | |
|---|---|--|
| <p>AIRGENS CS12A1-1 (12 BAR) PRESSURE SWITCH (1 PORT)</p>  <p>1404020911002</p> <p>AIRGENS CS12A3-1 (12 BAR) PRESSURE SWITCH (4 PORT)</p>  <p>1404020911001</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 110 PSI ~ 150 PSI OPERATING PRESSURE: 70 PSI ~ 175 PSI DIFFERENTIAL PRESSURE: 30 PSI</p> <p>FOUR PORT: G-1/4"</p> |
|---|---|--|




LEFOO LF-10 PRESSURE SWITCH (150 PSI) C/W UNLOADER VALVE & AUTO-OFF DISCONNECT LEVER.

| | | |
|---|---|--|
| <p>LEFOO LF10 (35 PSI~150 PSI) PRESSURE SWITCH (1 PORT) C/W UNLOADER VALVE</p>  <p>1404012471003</p> <p>LEFOO LF10 (35 PSI~150 PSI) PRESSURE SWITCH (4 PORT) C/W UNLOADER VALVE</p>  <p>1404022471003</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 85 PSI ~ 115 PSI DIFFERENTIAL PRESSURE: 30 PSI ~ 40 PSI OPERATING PRESSURE: 35 PSI ~ 150 PSI ELECTRICAL RATING: 12A/240VAC</p> <p>FOUR PORT: G-1/4"</p> |
|---|---|--|




LEFOO LF-10A PRESSURE SWITCH (150 PSI) C/W UNLOADER VALVE & AUTO-OFF DISCONNECT LEVER.

| | | |
|--|--|--|
| <p>LEFOO LF10A (35 PSI~150 PSI) PRESSURE SWITCH (1 PORT) 26A/240VAC</p>  <p>1404012470007</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 85 PSI ~ 115 PSI DIFFERENTIAL PRESSURE: 30 PSI ~ 40 PSI OPERATING PRESSURE: 35 PSI ~ 150 PSI ELECTRICAL RATING: 26A/240VAC</p> |
|--|--|--|




LEFOO LF-10 PRESSURE SWITCH (200 PSI) C/W UNLOADER VALVE & AUTO-OFF DISCONNECT LEVER.

| | | |
|---|---|---|
| <p>LEFOO LF10 (70 PSI~200 PSI) PRESSURE SWITCH (1 PORT)</p>  <p>1404012470001</p> <p>LEFOO LF10 (70 PSI~200 PSI) PRESSURE SWITCH (4 PORT)</p>  <p>1404022471001</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 130 PSI ~ 175 PSI OPERATING PRESSURE: 70 PSI ~ 200 PSI DIFFERENTIAL PRESSURE: 40 PSI ~ 55 PSI ELECTRICAL RATING: 12A/240VAC</p> <p>FOUR PORT: G-1/4"</p> |
|---|---|---|

LEFOO LF17 PRESSURE SWITCH (250 PSI) C/W UNLOADER VALVE & AUTO-OFF DISCONNECT LEVER.

| | | |
|---|---|--|
| <p>LEFOO LF17 (40 PSI~250 PSI) PRESSURE SWITCH (1 PORT)</p>  <p>1404012470005</p> <p>LEFOO LF17 (40 PSI~250 PSI) PRESSURE SWITCH (1 PORT) 3/8" Rc</p>  <p>1404012470008</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 145 PSI ~ 175 PSI OPERATING PRESSURE: 40 PSI ~ 250 PSI DIFFERENTIAL PRESSURE: 25 PSI ~ 60 PSI ELECTRICAL RATING: 20A/240VAC</p> <p>SINGLE (ONE) PORT: 3/8" Rc</p> |
|---|---|--|

LEFOO LF-19 PRESSURE SWITCH (14 BAR) C/W UNLOADER VALVE AND ON/OFF KNOB.

| | | |
|---|---|--|
| <p>LEFOO LF19 (5 BAR~14 BAR) PRESSURE SWITCH (1 PORT)</p>  <p>1404012470003</p> <p>LEFOO LF19 (5 BAR~14 BAR) PRESSURE SWITCH (4 PORT)</p>  <p>1404022471002</p> |  | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 7.5 BAR ~ 10 BAR OPERATING PRESSURE: 5 BAR ~ 14 BAR DIFFERENTIAL PRESSURE: 2.5 BAR ~ 4 BAR ELECTRICAL RATING: 26A(UL)/240VAC</p> <p>FOUR PORT: G-1/4"</p> |
|---|---|--|

| BAR CODE ITEM PART NO | PRODUCT PHOTO | DESCRIPTION & SPECIFICATION |
|--------------------------|------------------|--------------------------------|
|--------------------------|------------------|--------------------------------|

CONDOR MDR2/11 (GERMANY) PRESSURE SWITCH (12 BAR) C/W UNLOADER VALVE AND ON/OFF KNOB.

| | | |
|--|--|---|
| <p>CONDOR MDR 2/11 PRESURE SWITCH (1 PORT)</p> <p>1404010580001</p> <p>CONDOR MDR 2/11 PRESSURE SWITCH (4 PORT)</p> <p>1404020580001</p> | | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 110 PSI ~ 150 PSI OPERATING PRESSURE: 60 PSI ~ 180 PSI DIFFERENTIAL PRESSURE: 30 PSI ~ 40 PSI</p> <p>FOUR PORT: G-1/4"</p> |
|--|--|---|

3-PHASE (400V) CONDOR MDR4/11 PRESSURE SWITCH (12 BAR) C/W UNLOADER VALVE AND ON/OFF KNOB.

| | | |
|---|--|---|
| <p>CONDOR MDR 4/11 PRESSURE SWITCH</p> <p>1404010590003</p> | | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 110 PSI ~ 150 PSI OPERATING PRESSURE: 60 PSI ~ 180 PSI DIFFERENTIAL PRESSURE: 30 PSI ~ 40 PSI</p> |
|---|--|---|

3-PHASE (400V) AIRCON AR-13VX PRESSURE SWITCH (213 PSI) C/W UNLOADER VALVE AND ON/OFF KNOB.

| | | |
|---|--|--|
| <p>IR INDIA AIRCON PRESSURE SWITCH 10 0~213 PSIG (AR-13VX)</p> <p>1302010651001</p> | | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 130 PSI ~ 175 PSI OPERATING PRESSURE: 100 PSI ~ 213 PSI DIFFERENTIAL PRESSURE: 30 PSI ~ 40 PSI</p> |
|---|--|--|

3-PHASE (400V) LEFOO LF-18 PRESSURE SWITCH (16 BAR) C/W UNLOADER VALVE AND ON/OFF KNOB.

| | | |
|---|--|--|
| <p>LEFOO LF18 (4 BAR~16 BAR) 3-PHASE (4 OOV) PRESSURE SWITCH</p> <p>1404012470002</p> | | <p>SINGLE (ONE) PORT: G-1/4"</p> <p>FACTORY SETTING: 8 BAR ~ 10 BAR OPERATING PRESSURE: 4 BAR ~ 16 BAR DIFFERENTIAL PRESSURE: 1.8 BAR ~ 4.5 BAR</p> <p>ELECTRICAL RATING: 25A/400VAC</p> |
|---|--|--|

LEFOO LF-5532E PRESSURE SWITCH (32 BAR) FOR AIR COMPRESSOR (MAXIMUM OPERATING PRESSURE: 35 BAR).

| | | |
|---|--|---|
| <p>LEFOO LF55 (8 BAR~32 BAR) PRESSURE SWITCH</p> <p>1404012470004</p> | | <p>G-1/4" MALE BSP THREAD</p> <p>FACTORY SETTING: 17 BAR ~ 20 BAR OPERATING PRESSURE: 8 BAR ~ 32 BAR DIFFERENTIAL PRESSURE: 2 BAR ~ 6 BAR</p> |
|---|--|---|

LEFOO LF-5530MS PRESSURE SWITCH (30 BAR) FOR AIR-COND / AIR DRYER (MAX OPERATING PRESSURE: 35 BAR).

| | | |
|---|--|--|
| <p>LEFOO LF55 (8 BAR~30 BAR) PRESSURE SWITCH</p> <p>1404012470006</p> | | <p>1/4" FLARE NUT ϕ 2.4X1.000 CAPILLARY TUBE</p> <p>FACTORY SETTING: MANUAL RESET ~ 20 BAR OPERATING PRESSURE: 8 BAR ~ 30 BAR DIFFERENTIAL PRESSURE: \leq 4 BAR</p> |
|---|--|--|

UNLOADER VALVE FOR PRESSURE SWITCH (PREVENTS COMPRESSOR FROM STARTING UNDER LOAD)





| | | |
|---|--|--|
| <p>UNLOADER VALVE FOR PRESSURE SWITCH (TOP MOUNTED)</p> <p>1404062473001</p> | | <p>UNLOADER VALVE FOR PRESSURE SWITCH (TOP MOUNTED)</p> |
| <p>UNLOADER VALVE FOR PRESSURE SWITCH (BOTTOM MOUNTED)</p> <p>1404062473002</p> | | <p>UNLOADER VALVE FOR PRESSURE SWITCH (BOTTOM MOUNTED)</p> |

| BAR CODE ITEM PART NO | PRODUCT PHOTO | DESCRIPTION & SPECIFICATION |
|--------------------------|------------------|--------------------------------|
|--------------------------|------------------|--------------------------------|





AUXILLIARY UNLOADER VALVE

| | | |
|--|---|--|
| AIRGENS 1/2" AUXILLIARY UNLOADER VALVE (150 PSI)  1405010910001 |  | CONNECTION: 1/2 INCH FACTORY SETTING: 85 PSI ~ 115 PSI OPERATING PRESSURE: 100 PSI ~ 150 PSI |
|--|---|--|



IR AUXILLIARY UNLOADER VALVE

| | | |
|---|---|---|
| AUXILLIARY UNLOADER VALVE (150 PSI) 40100014  1405010130001 |  | CONNECTION: 1/4 INCH FACTORY SETTING: 110 PSI ~ 150 PSI OPERATING PRESSURE: 80 PSI ~ 200 PSI |
| IR AUXILLIARY UNLOADER VALVE (3217 0771)  1302012011001 |  | CONNECTION: 1/4 INCH FACTORY SETTING: 130 PSI ~ 175 PSI OPERATING PRESSURE: 100 PSI ~ 232 PSI |



HEAVY DUTY AUXILLIARY UNLOADER VALVE

| | | |
|--|--|---|
| IR INDIA AUXILIARY UNLOADER VALVE 1 5 BAR (90~260 PSIG)  1302010651002 |  | CONNECTION: 1/4 INCH FACTORY SETTING: 130 PSI ~ 175 PSI MAXIMUM OPERATING PRESSURE: 260 PSI |
| IR INDIA AUXILIARY UNLOADER VALVE 4 0 BAR (300~600 PSIG)  1302010651003 |  | CONNECTION: 1/4 INCH FACTORY SETTING: 130 PSI ~ 175 PSI MAXIMUM OPERATING PRESSURE: 600 PSI |



ENGINE UNLOADER VALVE

| | | |
|---|---|--|
| ENGINE UNLOADER VALVE  1405040911001 |  | CONNECTION: 1/4 INCH FACTORY SETTING: 85 PSI ~ 115 PSI MAXIMUM OPERATING PRESSURE: 175 PSI |
|---|---|--|

2-WIRE CONNECTION PRESSURE TRANSDUCER FOR ROTARY SCREW AIR COMPRESSOR

| | | |
|---|---|--|
| 2-WIRE CONNECTION PRESSURE TRANSDUCER  1305022470001 |  | MODEL: T-2000 PRESSURE RANGE: 0 ~ 16 Bar OUTPUT: 4 ~ 20 Ma ACCURACY: 1.0% WORKING TEMPERATURE: -40°C ~ 100°C PROTECTION GRADE: IP 67 CONNECTION: G-1/4" MALE C/W CABLE: 1 Meter |
|---|---|--|

PACKARD CONNECTION PRESSURE TRANSDUCER FOR ROTARY SCREW AIR COMPRESSOR

| | | |
|--|---|--|
| PACKARD CONNECTION PRESSURE TRANSDUCER  1305022470002 |  | MODEL: T-210 PRESSURE RANGE: 0 ~ 16 Bar OUTPUT: 4 ~ 20 Ma ACCURACY: 1.0% WORKING TEMPERATURE: -40°C ~ 100°C PROTECTION GRADE: IP 67 CONNECTION: G-1/4" MALE C/W PACKARD CONNECTOR |
|--|---|--|