PRODUCT DATASHEET

Legend[™] Thermal Tie-On Cable Labels





ONE SOFTWARE

ONE PRINTER

ONE RIBBON





Our low cost Legend[™] polyester thermally printed tie-on cable labels offer a simple way of printing either low volumes in ones or twos or in higher volumes in conjunction with the Fox-in-a-Box® DTP-1/300 thermal printer.

Print 100 tie-on cable labels in 100 seconds!

It has been independently tested for salt mist spray, high/low temperature, H₂S, humidity - so can be used where a thermal solution is preferred and there is no requirement for LS0H or UV resistance.

Authorised for use for London Underground Limited projects.

TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer	
Thermal Ribbon	Silver Fox TSR3	
Material	Polyester	
Thickness	175 microns	
Standard Colours	Yellow	
Standard Sizes	90mm x 13mm	
RoHS (EU 2002/95/EC)	RoHS Compliant	

PRODUCT TESTING

Test	Method		
Moisture Resistance	MIL-STD-202G Method 106G		
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4		
High Temperature 2000 hours @ 70°C to 100°C*	MIL-STD-202G Method 108A		
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)		
UV Weathering 500 hours**	ISO 4982 Part 3 Method A Cycle 1		
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)		

^{*}Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C **Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for use internally such as: data centres, control rooms, sub-stations, power stations etc. Other applications may include banks, hotels airports etc

SINGLE STATE OF THE PARTY OF TH

DELTA SAMA JAYA SDN BHD (DSSB) (REG. NO: 500276-W)

No 23G & 23M, DSSB Building, Jalan Perdana 6/8, Pandan Perdana, 55300 Kuala Lumpur.
Tel: +603 9286 6328, +603 9281 3778 Fax: +603 9287 0705
Email: samajaya@substation.com.my, sales@substation.com.my | Website: www.substation.com.my

Member of:







FEATURES & BENEFITS

- Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm unlimited

APPROVALS

 Authorised for use by London Underground Registration No. 1105

Print using our DTP – 1/300 Thermal Printer.



PRODUCT DATASHEET

Legend[™] Thermal Tie-On Cable Labels





ONE SOFTWARE

ONE PRINTER

ONE RIBBON





STORAGE INSTRUCTIONS

Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)		
Shelf Life	2 Years		
Conditions	Keep in dark conditions		
Humidity Resistance	35% to 65% RH		


HOW TO REMOVE LABELS

STEP 1



After printing, fold the label along the perforations

STEP 2



Firmly crease along the fold

STEP 3



Tear along the crease to remove the label

ORDER INFORMATION

Product Code	Label Dims (mm)	Labels / Roll	Rolls / Pack	Labels / Pack	Colour Options
LM9013TY	90 x 13	3000	1 Roll	3000	

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted.

This datasheet supersedes any previous information/datasheet released and is subject to change without notice.

Use with Silver Fox Labacus Innovator Advanced or Professional software. Print in conjunction with

Print in conjunction with our Fox-in-a-Box Plug'N'Play thermal printer using the same ribbon as all our other thermal labels.

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE





DELTA SAMA JAYA SDN BHD (DSSB) (REG. NO: 500276-W)

No 23G & 23M, DSSB Building, Jalan Perdana 6/8, Pandan Perdana, 55300 Kuala Lumpur. Tel: +603 9286 6328, +603 9281 3778 Fax: +603 9287 0705

Email: samajaya@substation.com.my, sales@substation.com.my | Website: www.substation.com.my

Member of:





