

HayTemp 1700

Art. no. 611377 Hay thermometer

Stored hay or straw, etc. is prone to overheating (depreciation) or even self-ignition, because of biological processes. This problem is even emphasized with higher moisture contents. Therefore a regular temperature check is crucial. The HayTemp 1700 optimally supports farmers as well as firefighters.

Application:

Hay or straw measurements at depth up to 4 m.

Specifications	ļ
----------------	---

Measuring rod:

Device: G 1700

BNC, Pt1000, 2-wire Probe connection:

Fiberglass probe, approx. 4 m long, approx. 10 mm Ø,

1 measuring point at probe tip

Cutting tip: screwable, double-edged tip with integrated temperature

Weight: Measuring rod with cutting tip approx. 600 g

Device, fiberglass rod, probe tip Pt1000, BNC cable (1.5 m), Scope of supply:

battery, manual

Accessories and spare parts:

G 1700

Art. no. 609826

Precise universal thermometer, with BNC connection, without sensor

Fiberglasrohr

Art. no. 604407

4 m, without probe and without tip

Sondenspitze

Art. no. 606889

With integrated temperature sensor

Kabel BNC/BNC

Art. no. 602855

Connection cable with 1.5 m length

ST-G1000

Art. no. 611373

Device protection bag with 1 round cut-out

Instruments for hay and straw humidity measurements: see BaleCheck page 51!

SOIL THERMOMETER



Soil thermometer

The universal display device combined with an extremely robust, but yet ergonomic T-handle probe made of stainless steel allows multiple measurements in soils or bulk materials.

Silo checking, measurements in soils, waste dumps, silages, compost, etc.

Specifications:	
Device:	G 1700
Probe connection:	BNC, Pt1000, 2-wire
Measuring range:	-50.0 +250.0 °C
Measuring rod:	Stainless steel, 1000 mm x \emptyset 10 mm, 1 m connection cable with BNC plug, 350 g, probe handle designed for comfortable use
Scope of supply:	Device, GTF 40 T, battery, manual

Accessories and spare parts:

G1700

Art. no. 609826

Precise universal thermometer, with BNC connection, without sensor

GTF 40 T-620

Art. no. 606803

Stainless steel insertion probe, FL 620 mm, with 1 m cable and BNC plug

GTF 40 T-1000

Art. no. 606791

Stainless steel insertion probe, FL 1000 mm, with 1 m cable and BNC plug

GTF 40 T-1500

Art. no. 606792

Stainless steel insertion probe, FL 1500 mm, with 1 m cable and BNC plug

ST-G1000

Art. no. 611373

Device protection bag with 1 round cut-out