

DIESEL ENGINE OIL MONO CF 30

MONO ENGINE OIL CF 30 is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions. MONO ENGINE OIL CF 40 is suitable for use in a wide range of on- and off-high- way applications where an API CF oil is recommended. MONO ENGINE OIL CF 40 is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties: • High thermal and oxidation stability. • Effective in preventing from wear, corrosion and foam. • High dispersancy and detergency properties.

BENEFITS:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

Exceeds: API SF/CF, MTU Type 2, CCMC G2/D1, MIL-L-46152

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	30
Density@15°C	kg/m ³	ASTM D4052	895
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	93
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.7
Viscosity Index		ASTM D2270	98
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	12.7