

SUPER TRACTOR OIL 10W-30

SUPER TRACTOR OIL 10W-30 is a high quality universal mineral based so cal- led “Super Tractor Oil Universal” (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed “wet brakes”. This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF). SUPER TRACTOR OIL 10W-30 is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following pro- perties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

Available in 18L and 200L

Exceeds: Engine Spec: API CG-4/CF-4/CE/SF, MB 227.1, ACEA E3, UTTO Spec: JD J20C/D, Ford M2C86B/C, Ford M2C134D, CASE MS 1204/6/7/9, MF M1135/1139, MF M1143/1145, Cat TO-2, API GL-4, Allison C-4 Hydr Spec: Eaton M-2950S, Eaton 1-280-S, Danfoss

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-30
Density@15°C	kg/m ³	ASTM D4052	878
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.75
Viscosity Index		ASTM D2270	143
Viscosity CCS @-25°C, max	cP	ASTM D2983	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.5