



# JOTUN

## WOODSHIELD

TRUE WOOD PROTECTION



### Disclaimer

We have made every effort to make the colours on screen as close to actual paint colours as computer screen resolutions as allow. Please refer to paint chop samples for an accurate match. Colours will vary depending on your screen settings and resolution. Applied sample is recommended when colour matching is critical.

# GOLDEN SAND

The golden tone of the forest, symbolizes the richness and toughness of the woods. Truly a fruit of life.

*Matt*

*Gloss*




Autumn Oak

9087

*Matt*

*Gloss*



Teak

9088



Golden Pine

9089



Maize

9090



Chestnut

9091



Maple

9092



Almond

9093



Walnut

9094



"Colours shown represent Jotun Woodshield on meranti wood. All colours reproduced are shown as close to actual colours as modern printing techniques allow. Final result varies depending on colour, texture, grain, porosity and type of wood. Where colour matching is critical, an applied sample is recommended."

## FOREST WALK

Natural red and green elements of the forest path inspire ways to beautify the timber grain.


*Matt*

*Gloss*




Mint

9712




Clover

9714



Cherry Red

9139



Rosewood

9141

*Matt*

*Gloss*




Parsley

9713




Cedar

9138



Mahogany

9140



## VARNISH

Transparent finish captures and preserves the natural elegance of the earthy wood.

*Matt*

*Gloss*






*Matt*
*Gloss*


Bronze Yellow

9095



Nyatoh

9144

*Matt*
*Gloss*


Sunset

9142




Buckeye

9145

*Matt*
*Gloss*



Acacia

9143




Palisander

9146



Carbon Grey

9147



Ebony

9096

## SEMI-OPAQUE SHADES

Inspirations from season change, colours from spring to fall; opaque shades bestow solid colour textures that are easily simulated and sustained for years to come.



# WOODSHIELD

TRUE WOOD PROTECTION



## Woodshield Exterior



Woodshield Exterior has been specifically formulated with 2X UV Protection, good flexibility and deep penetration into the wood. It protects the wood 2X longer than conventional wood finish products.

Suitable for all exterior wood such as doors, trims, frames, trellis, fences, railings, roofs, windows and balconies.

Available in Multicolor Tintable Stains and Varnish, in Gloss and Matt



### 2X Longer Performance

- Provide protective barrier against harsh weather for longer lasting, durable wood protection.



### 2X UV Protection

- Minimise colour fading and protection against wood crack, peel and erosion from sunlight to save time and money on maintenance.



### Low Odour

- Painting made pleasant, thanks to less smell during and after application.



## Woodshield Interior



Woodshield Interior is formulated to create a smooth and tough film that facilitates everyday use and cleaning of the wood surface. Its low odour formulation means less smell during and after the wood finishing process.

Suitable for all interior wood such as doors, trims, railings, windows, furniture, cupboards and frames.

Available in Multicolor Tintable Stains and Varnish, in Gloss and Matt



### Easy Clean

- Effortless washing that keeps wood clean and beautiful.



### Fast Drying

- Convenient and quick drying solution that saves time, energy and manpower.



### Low Odour

- Painting made pleasant, thanks to less smell during and after application.

## Woodshield Deck



Woodshield Deck is the ultimate protection for wood surfaces that are exposed to the elements as well as frequent wear and tear. It provides a tough, scratch resistant film that is flexible enough to meet wood expansion and contraction requirements.

Suitable for all exterior wooden decks, interior wooden floors/parquet, outdoor/garden furniture and all wood fixtures exposed to frequent use.

Available in Multicolor Tintable Stains and Varnish, in Gloss and Matt



### Scratch Resistance

- Reduce visible scratches and marks for enduring natural wood beauty without need for frequent wood finishing maintenance.



### 2X UV Protection

- Minimise colour fading and protection against wood crack, peel and erosion from sunlight to save time and money on maintenance.



### Fast Drying

- Convenient and quick drying solution that saves time, energy and manpower.



### Low Odour

- Painting made pleasant, thanks to less smell during and after application.

## Additional Features for All Woodshield Range



### Good Flexibility

- Withstands constant wood expansion and contraction that minimises undesired effects like cracking; therefore, protecting and preserving wood investment.



### Anti Fungal

- Prevents unsightly growth of surface fungus to maintain beautiful, healthy wood.



### Water Resistance

- Prevents moisture absorption for prolonged wood life and preserved natural warmth and beauty.



### Heavy Metals Free

- Non-hazardous and environmentally-friendly without compromising performance and beauty.
- Does not contain Lead, Mercury, Chromium, Cadmium and Arsenic.



# WOODSHIELD

TRUE WOOD PROTECTION

## Painting Guide

Wood surface must be suitably prepared, clean, dry and free from traces of dust, dirt, wax and grease. The moisture content should not exceed 15% prior to coating.

*Optional Step:- Wash with Jotun Fungicidal Wash to prevent and remove fungus growth on the wood. Leave it to dry for 24 hours before proceeding with Step 1.*

### STEP 1



- Sand the surface of the wood thoroughly with #400 grit sand paper.

### STEP 2



- Wipe the wood surface with a cloth dampened with Jotun Gardex Thinner to remove dust and particles. Allow it to dry fully before painting.

### STEP 3



- Apply 1 coat of Woodshield. Please refer below table for recommended recoating time.

Step 4: Repeat steps 1, 2, 3 using #600 grit sand paper after 1st coat of Woodshield.

### For new wood

Step 5: Repeat again steps 1, 2, 3 using #1000 grit sand paper after 2nd coat of Woodshield.

	Woodshield Exterior	Woodshield Interior	Woodshield Deck
Drying Time (Hours)	3-4	1-2	1-2
Recoating Time (Hours)	8	4	4
Coverage	14-16 m <sup>2</sup> /litre	12-14 m <sup>2</sup> /litre	12-14 m <sup>2</sup> /litre
Thinning	Dilution is not necessary for brush and roller application. If required, dilute with Jotun Gardex Thinner (max 5%). For spray application, dilute with Jotun Gardex Thinner (max 15%).		
Application	Brush, roller or air spray.		
Cleaning	Clean brushes and tools with Jotun Gardex Thinner.		

# WOODSHIELD

TRUE WOOD PROTECTION



## EXTERIOR

Deep Penetrating Resin with Advanced UV Absorbers

## INTERIOR

Enhanced Drying Time with Urethane Alkyd Technology

## DECK

Urethane Alkyd Technology with Advanced UV Absorbers

### TECHNOLOGY



2X LONGER PERFORMANCE



2X UV PROTECTION



EASY CLEAN



FAST DRYING



LOW ODOUR



SCRATCH RESISTANCE



GOOD FLEXIBILITY



ANTI FUNGAL



WATER RESISTANCE



HEAVY METALS FREE



#### JOTUN ASIA PACIFIC

**MALAYSIA**  
JOTUN (MALAYSIA) SDN. BHD.  
Lot 7, Persiaran Perusahaan, Seksyen 23,  
40300 Shah Alam, Selangor, Malaysia.  
Tel: +603 5123 3500

**SINGAPORE**  
JOTUN (SINGAPORE) PTE. LTD.  
37 Tuas View Crescent,  
Singapore 637236.  
Tel: +65 6598 8288

jotun.com/ap

**CHINA**  
JOTUN COATINGS (ZHANGGANG) CO. LTD.  
Floor 20, Jiu Shi Mansions,  
No. 28, Zhong Shan Road (South), Shanghai, China.  
Tel: +86 21 63330800

**THAILAND**  
JOTUN THAILAND LTD.  
49/26, Moo 12, Kingkaew Road, Rajataewa  
Bangkapi, Samutprakarn 10540, Thailand.  
Tel: +66 2760 3305

**INDONESIA**  
PT. JOTUN INDONESIA  
Kawasan Industri MM 2100, Blok KK-1,  
Cikarang Barat, Bekasi 17520, Indonesia.  
Tel: +62 21 8998 2637

**VIETNAM**  
JOTUN PAINTS (VIETNAM) CO. LTD.  
No. 1 Street 10, Song Than 1 Industrial Zone,  
Di An District, Binh Duong Province, Vietnam.  
Tel: +84 650 3742206



Jotun Protects Property