

LED DOWNLIGHT PASKA SQUARE

LED DOWNLIGHT PASKA SQUARE comes with aluminum diecasting housing design, with the availabilities of few version of reflector design, enable customers to choose the light fitting appearance with their preference.

Downlight PASKA is designed to spread out evenly and smoothly down the wall with high lumen output, creating the perfect glare-less lighting effect. It provides high efficiency optics and light pattern that is suitable in any commercial application.

FEATURES

- System Power : 12W, 22W 32W & 42W
- Beam Angles : 55°
- CCT : 3000K , 4000K & 6500K
- CRI : >90
- IP rating : IP44
- Dimming : 0-10v / DALI (optional)

HIGHLIGHTS

- Easy Installation and maintenance
- LED Light Source: CREE / CITIZEN
- Average rated lifespan of 50,000 hours
- Flickering free
- Instant-On Light

CERTIFICATIONS

- CE
- RoHS


TECHNICAL SPECIFICATIONS

System Power	CCT	Beam Angles	Light Output	CRI	Dimension A X B (mm)	Reflector	Article Number
12W	3000/4000/6500K	55°	1200lm	>80	60 x 115	Mirror	HC-DV-E6N-NxFVDL
22W	3000/4000/6500K	55°	2000lm	>80	75 x 140	Mirror	HC-DV-cHU-NxFVDL
32W	3000/4000/6500K	55°	3000lm	>80	80 x 160	Mirror	HC-DV-Fq6-NxFVDL
42W	3000/4000/6500K	55°	4000lm	>80	85 x 195	Mirror	HC-DV-Lr9-NxFVDL

Option : **x: CCT**
 C=3000K
 D=4000K
 a=6500K



TECHNICAL DRAWING



Tolerance: ±2.5mm

RADIATION PATTERNS

