



# Experience the superb in LA VIE Alarm System.

Wired & Wireless Alarm



- HOUSE
  - CONDOMINIUM
  - OFFICE BUILDING
  - SHOPPING COMPLEX
- HOTEL
- FACTORY

The remarkable New Classic La Vie L Series has elevated the standard in traditional security. This is the most advanced, software-driven 8 and 16-zone system available, offering the broad range of security features and functions you need for protection of lives and property, whether at home or at work. Created through leading-edge technology, the L Series is designed with the most modern, hybrid wireless and hardwired security and fire protection. It offers a new level of alarm communications for your protection and it incorporates sophisticated false-alarm prevention features. The L Series has been rigorously designed for easy customization, for exceptional ease of use and for proven reliability. With its powerful capability for improving the protection of lives and possessions, the New Classic L Series truly has become the ultimate standard for a wide variety of traditional security demands.

# Choosing the Right Security System for You!!

### Model L8

L8 comprise of 8 programmable zones, it has memory function, so that the programmed parameters and the information of the control panel's condition would not lose when power is cut. The function is perfect, the programming is convenient, the installation is easy, and the usage is safe. It supports programming any address information at will. It could greatly reduce the working time of installation and programming.

### **General Feature:**

- 9 user codes including Master code,
  - Programmable 8 zones with end-of-line supervisory
    - Individual delay zone, hand-over zone, instant zone and 24-hour zone
      - Individual zone Bypass function
        - Individual Chime zone and sensitivity level
          - Walk-test function
            - System Test function
            - Duress alarm for CMS reporting
              - Dual reporting for CMS and Personal format
                - CMS reporting in Contact ID format
                  - 4 Personal reporting dialing numbers
                  - I CMS account number
                  - Programmable 8 wireless zone.\*

\* Optional Item



## Model L16(V)





L16(V) is a full-featured security system that uses advanced technology for burglary, fire and environmental detection. L16(V) is a flexible security system that is easy to install and simple to use. Feature with four PGM output for advance Home automation control. With two partitions and up to 16 zones, L16(V) can handle most medium residential and commercial security needs.

### **General Feature**

- Support up to 8 user codes
- Programmable 16 zones with end of line supervisory
- 2 partition programming
- Support up to 6 keypad
- Built-In GSM and SMS reporting capability \*
- Telephone Voice feedback
- 4 PGM Home Automation Output
- 2 Intelligent zones to minimize false alarm
- Keypad lock setting
- Superb lightning protection
- Walk test function
- System test function
- Duress Alarm for CMS reporting
- CMS reporting in Contact ID format
- I CMS account and programmable 2 CMS number
- 4 personal reporting dialing numbers
- Programmable 16 wireless zone.\*

\* Optional Item

| CONTROL PANEL | (FRANCE) |
|---------------|----------|
|---------------|----------|

| EATURES   | LA VIE 8  | LA VIE 8(V) | LA VIE 16 |
|---|-----------|-------------|-----------|
| rogrammable zones   | 8         | 8           | 16        |
| one partition   | -         | 2           | 2         |
| laid partition  | -         | Y           | Y         |
| lser code including Master & Installer code                   | 9         | 9           | 9         |
| way/Home arming mode  | Y         | Y           | Y         |
| elay, Instant, Handover, 24 hours                             | Υ         | Y           | Y         |
| ulse  | Υ         | Y           | Y         |
| rogrammable Exit and Entry delay                              | Υ         | Y           | Y         |
| ey-switch arm and disarm                                      | Υ         | Y           | Y         |
| ndividual Door Chime mode                                     | Y         | Y           | Y         |
| orce arming   | γ         | Y           | Y         |
| ndividual zone sensitivity                                    | Υ         | Y           | Y         |
| ndividual zone bypass   | Y         | Y           | Y         |
| ntelligent zone counter                                       | -         | Y           | Y         |
| rogrammable arm and disarm siren squawk                       | Y         | Y           | Y         |
| rogrammable force arming siren warning                        | Y         | Y           | Y         |
| one alarm memory review mode                                  | Y         | Y           | Y         |
| Dureless alarm  | Y         | Y           | Y         |
| uto daily test  | Y         | Y           | Y         |
| Jual reporting  | Y         | Y           | Y         |
| MS Reporting  | _         |             | optional  |
| uild In GSM Module  | -         | -           | optional  |
| ontact ID for CMS reporting format                            | Y         | Y           | Y         |
| lumber of programmable CMS telephone numbers                  | 2         | 2           | 2         |
| lumber of programmable Personal telephone numbers             | 4         | 4           | 4         |
| luber of CMS account  | 1         | 1           | 1         |
| emote access to arm/disarm                                    | Y         | Y           | Y         |
| ax bypass option  | Y         | Y           | Y         |
| ail to communicate output                                     | Y         | Y           | Y         |
| olice, Medical emergency                                      | Y         | Y           | -         |
| ire emergency   | Y         | Y           | Y         |
| anic emergency  | Y         | Y           | Y         |
| uto arming and disarming                                      | Y         | Y           | Y         |
| eypad lockout   | Y         | Y           | Y         |
| nti takeover  | Y         | Y           | Y         |
| oice-assisted programming                                     | -         | Y           | Y         |
| ersonal reporting format in voice                             |           | Y           | Y         |
| ersonal reporting format in beeping tones                     | Y         | _           | -         |
| ome Automation with feedback (PGM output)                     | I         | 4           | 4         |
| ndividual selection of latch or momentary for Home Automation | -         | Y           | 4<br>Y    |
| rogrammable Home automation output to activate upon alarm     | -         | Y           | Y         |
|   | -         | T           | T         |
| eing triggered  |           | V           | V         |
| uto ON/OFF of Home Automation output                          | -         | Y           | Y         |
| OPTIONAL ITEM   | 0         | 0           | 16        |
| /ireless zone   | 8         | 8           | 16        |
| ransmission range   | 100 meter | 100 meter   | 100 meter |
| attery type   | Lithium   | Lithium     | Lithium   |
| SPECIAL FEATURE   |           |             |           |
| 'Spy Now' Function  |           |             |           |
| Voice Activated Alarm   |           |             |           |

\* Specifications are subject to change without prior notice.

