









<u>Model No.</u>	<u>Product Description</u>	<u>Picture for reference</u>
MP-7070 (35w)	<ul style="list-style-type: none"> ◆ with a preamplifier, with one microphone input, high and low adjustable ◆ two-way input, two-way output, radio, SD card, USB interface, CD/ audio source and telephone. ◆ microphone and circuit, Mp3 volume can be independently adjustable. ◆ with short circuit, overload, overheating, and other protection ◆ with bluetooth function 	
QG-P060AT (60w) QG-P100AT (100w) QG-P150AT (150w) QG-P250AT (250w)	<p style="text-align: center;"> Power:60W/100W/150W/250W/350W/500W/650W Case:Iron Case; Iron Panel; Iron Handle;Plastic knob I/O:2 MIC IN; 2 AUX IN; USB IN; SD IN 1 AUX OUT Speaker Output:COM/4-16ohm/70V/100V; COM/100V for 5 Zones Each Channel:6 Zones with Adjustable Knob Tune:2 Bands Control - Treble, Bass MP3:Bluetooth; FM Radio; Remote Controller. Amplifier Type:CLASS AB: Acoustics:Frequency Response: 80HZ-18KHz; THD: <1% at 1/3 Voltage Protection:Full Protection(Short Circuit; Over Load; Over Current; DC Fault); Addition:CHIME Button; AUX1/USB and AUX2 Selectable; Newest Class AB Amplifier, High efficiency with quality sound; Costeffective price;Power limit when overload: </p>	   
CS-06A (1.5w/3w/6w) VTX-620 (30w/40w) CLS-958 (10w-35w)	<p> Rated power: 1.5W-3W-6W Sensitivity: 90dB Frequency response: 100Hz-15KHz Woofer Size:6.5" 160mm Woofer Magnet:45*10mm Woofer Cone: Paper Cone 13mm External dimensions: 195*55mm Hole size: 160mm </p> <p> Rated power: 30-40W Sensitivity: 92dB Frequency response: 80Hz-18KHz Woofer Size:6.5" Woofer Magnet:70*15mm Woofer Cone: Kevlar Cone External dimensions: 236*130mm Hole size: 220mm </p> <p> Rated power: 10-35W Rated Voltage: 70V-120V Sensitivity: 92dB Frequency response: 55Hz-20KHz Woofer Size:5.25"132mm Woofer Cone:Black-Red Hybrid Woven Pot Tweeter:Coxial Tweeter; Silk Diaphragm External dimensions: 196*77mm Hole size: 175mm High Quality 100V Ceiling speaker with Coxial Tweeter and Crossover Board: </p>	  

<p>WS-632 (5w/10w)</p>	<p>Rated power: 5W-10W Sensitivity: 95dB Frequency response: 80Hz-18KHz Woofer Size:6" Tweeter:3" Woofer Cone: Paper Cone Dimensions: 272*182*125mm</p>	
<p>WS-608 (10w/20w)</p>	<p>Rated power: 10W-20W Sensitivity: 92dB Rated voltage: 70-120V Case Material: ABS Woofer Size: 4" Tweeter:2" Tweeter Cone:Polypropylene Cone, Foam Edge Frequency response: 65Hz-20KHz Speaker unit: 4inches Size: 174 * 118 * 265mm</p>	
<p>FT-505 (3.8/7.5/15/30w)</p>	<p>Rated power:30W Sensitivity: 92dB Rated voltage: 70-120V Case Material: ABS Woofer Size: 5.25" Tweeter:1(25.4mm) Titanium Fabric Dome Cone:Polypropylene, Rubber Suspension Frequency response: 65Hz-20KHz Speaker unit: 5.25inches Size: 163x237x160mm</p>	<p>Black color</p> 
<p>YH-30 (25w/30w)</p>	<p>Rated power:25W-30W Sensitivity: 92dB Rated voltage: 70-120V Frequency response: 300Hz-8KHz Dimension: 285x285x205mm</p>	
<p>F31 With Chime/Music</p>	<p>Capacitor Conference microphone Main Parameters Plastic Base << Capsule Type: Condenser << Frequency Response: 40HZ-16KHz << Polar Pattern: cardioid << Output Impedance: 2000 << Sensitivity: -40dB+2dB << Power supply: DC3V/ AC220V << Reference sound-receiving distance: 50cm << With indicative music(When opening or closing, with << Cable: 7m single-core cable, female XLR+ 6.35 mono plug << Switch: self-locking switch</p>	
<p>VC-30 (30w)</p> <p>VC-100 (100w)</p>	<p>Volume Control 100V type 30w/100w</p>	