

## VTH1520AS-H

IP Indoor Monitor



Technical Specification	
Model	VTH1520AS-H
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Audio	
Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
LCD Screen	7" 800x480, Resisitive
Operation Mode	
Input	Mechanical buttons
Interface	
Alarm In	8
Alarm Out	-
RS485	-
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Memory Slot	Embedded 8GB

## **Features**

- 7" TFT Resistive touch screen
- · IPC surveillance
- · Alarm integration
- $\cdot$  8GB SD card embedded
- · Record & Snapshot























Installation	Flush
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby ≤1.5W, Work ≤7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	257.8mm×261.4mm×33.5mm
Weight	0.8Kg

## Dimensions View Area





## Application

