

SI01 WiFi Module



· Dual wifi bandwidth: 2.4GHz / 5GHz

Using new generation 11AC, wireless transmission rate
could reach up to 433Mbps on 5GHz wifi bandwidth
Auto adjust the bandwidth to avoid crowd bandwidth and
channel interference, to get a more stable wifi

 \cdot Bluetooth 4.0: one to one pair to transfer files and data

Technical Specifications

Interface		
USB	1 x USB2.0	
Physical Specifications		
Antenna	1 x 2.4G for BT	
	1 x 2.4G or 5G for WiFi	
Main chipset	Realtek RTL8821AU-VS	
WiFi Standard	802.11 a/b/g/n/ac	
Bluetooth	Support 2.1/3.0/4.0	
Operating frequency	2.4G&5G(5150MHz-5250MHz&5725MHz-5825MHz)	
Modulation (WiFi)	11b: DBPSK, DQPSK and CCK and DSSS 11a/g: BPSK, QPSK, 16QAM, 64QAM and OFDM 11n: BPSK, QPSK,16QAM,64QAM and OFDM 11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM and OFDM	
Dimensions	77mm × 11mm × 99mm	
Net weight	30g	
Gross weight	80g	
Power		
Power supply	5V DC	
Power consumption	<2.5W	

Packing List	
Antenna	2pcs
Operating instruction	1pcs
Environment	
Operating conditions	$0^\circ\text{C} \sim +40^\circ\text{C}/10\%^\circ\!90\%\text{RH}^*$ Start up should be done at above 0°C
Storage conditions	-20°C~+60°C/10%~90% RH

Ordering Information			
Туре	Part Number	Description	
WiFi Module	SI01	WiFi Module	

Rev 001.001 © 2016 Dahua. All rights reserved. Design and specifications are subject to change without notice