

# PHRIA2.84-SH

Indoor Rental LED



## Features:

- The precision of die-casting aluminum cabinet splicing seam is less than 0.1mm.
- Special, adjustable locks achieve fast installation and uninstallation.
- Fanless design comes from superior heat dissipation.
- Good grey scale even at low brightness, brings profound levels and abundant colors.



## Technical Specification

### Model

Model	PHRIA2.84-SH
-------	--------------

### Parameters

Pixel Pitch(mm)	2.84
Module Size (W×H)	250×250mm
Module Resolution (W×H)	88×88
Pixel Type	1R1G1B
LED Type	SMD2020
Cabinet Size (W×H×D)	500×500×88mm
Cabinet Resolution (W×H)	176×176
Cabinet Material	Aluminium
Cabinet Weight (kg)	7.5
Cabinet Pixel Density (Pixels/Cabinet)	30,976
Brightness (nits)	≤800
Grey Level (bit)	12
Color (trillion)	0.068
Contrast	3000:1

Refresh Rate (Hz)	≥1920
Driving Mode	1/22 scan
Viewing Angle	140°/140°
Ingress Protection (front/rear)	IP30
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20℃~+50℃
Work Humidity	10%RH~90%RH
Recommended Viewing Distance (m)	≥6.5
Max Input Power (W/m <sup>2</sup> )	500
Avg Input Power (W/m <sup>2</sup> )	200
Signal Interface (compatible)	VGA,DVI,HDMI
Communication Connection	CAT5E:<100m, Single mode fiber:<10km
Maintenance Mode	Rear maintenance
Cabinet Fast Lock	Taperlock
Max Number of Hoisting Installation	15