

DS-PEA3M Series Pole Panic Alarm Station

DS-PEA3M series pole panic alarm station is designed with 2 MP HD camera, 2MP HD IR camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio, linking with the surrounding cameras and so on. It helps to realize alarm and aid as soon as possible and provides more efficient service for building social stability.

It is mainly applied to the scenarios of school, square, tourist attraction, hospital, supermarket gate, market, station, parking lot, etc.



Key Features

- Embedded Linux operation system
- High-performance embedded SOC processor
- Supports network adaptive and video and audio adaptive to realize low latency
- H.264、H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, SNMP, HIK-SIP, RTSP, and ONVIF
- Video collection and all-day monitoring with 2 MP HD camera
- Supports EHome for public network transmission
- Two-way audio function with up to 5 m communication distance; build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface



Specifications

| Model | DS-PEA3M Series Pole Panic Alarm Station | |
|----------------------------|--|--|
| System parameters | Processor | High-Performance Embedded SOC Processor |
| | Operation system | Embedded Linux Operation System |
| Build-in camera parameters | Camera | 2 MP HD IR Camera, IR Distance \geq 10 m |
| | FOV (Field of View) | Horizontal: 128° |
| | | Vertical: 75° |
| | | Diagonal: 147° |
| | Day & Night | IR Cut Filter |
| Video compression standard | H.264, H.264 SVC, H.265 | |
| | Resolution | 1920*1080@25fps |
| Audio parameters | Audio input | 1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input |
| | Audio output | 1-ch 30 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output |
| | Audio compression standard | G.711 U/64Kbps, G.726 /16Kbps |
| | Quality | Noise Reduction And Echo Cancellation |
| Alarm Parameters | Alarm Input | Tampering Alarm, One-Touch Alarm |
| Network parameters | Network protocol | TCP/IP, RTSP, SNMP, HIK-SIP, ONVIF |
| | Ethernet | 10 M/100 M Self-adaptive Ethernet Port |
| | Public network transmission | EHome, EZVIZ |
| | Network encryption | Supports User Lock-in and Password Security Prompt |
| Device interfaces | Network interface | 2 RJ45 10M/100M Self-adaptive Ethernet Port |
| | Switch (-H) | 8-port switch x 1 |
| | IO Input | 2 |
| | IO Output | 2 |
| | Alarm lamp | 1 Red and Blue Alarm Lamp, Light Can be Configured Separately |
| | Siren | 110dB, Sound Can be Configured Separately |
| | SD Card | Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G |
| | Lock | Electronic Controlled Cabinet Lock/Normal Cabinet Lock |
| | RS-485 | 1, Half-duplex |
| | PSTN | 1 |
| General | Power supply | 110-220V AC |
| | Power consumption | \leq 70 W |
| | Working temperature | -40 °C to +60 °C (-40 °F to 140 °F) |
| | Working humidity | 10% to 90% |
| | Installation | Ground Mounting |

Dimensions


Without Bracket: 450 mm × 500 mm × 2205 mm (17.72" × 19.69" × 86.81")
With Bracket: 450 mm × 500 mm × 4500 mm (17.72" × 19.69" × 177.17")

Available Models

DS-PEA3M-21

DS-PEA3M-21H

Typical Application



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (0) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com