

IPC-4300H

4.3 inch IPC Camera Tester



Function:

- ◆ 4.3 inch IPS test monitor with touch screen
- ◆ ONVIF
- ◆ DC12V 2A power output / DC 48V PoE power output
- ◆ HD TVI camera test
- ◆ IP discovery, Auto-search the whole network segment IP
- ◆ Auto -login and display the camera image, activate Hikvision camera quickly
- ◆ Hik test tool/ Hikvision camera brands test /IPC viewer

Model:

IPC-4300H

Application:

- CCTV system installation and maintenance
- Network cabling project installation and maintenance
- Dome camera IP camera testing
- Video transmission channel testing
- PTZ controller

Specification:

| Model | IPC-4300H |
|-------------------------------------|--|
| Display | 4.3 inch IPS LCD test monitor with touch screen , resolution 800 (RGB) x 480 |
| Network port | 10/100M auto adapt,RJ45 |
| WIFI | Built in WIFI,speeds150M,display wireless camera image |
| IP camera type | ONVIF, Hikvision. Customized welcome |
| IP discovery | auto-scan the whole network segment camera IP |
| Rapid ONVIF | search camera quickly, auto log in and display image from the camera, activate Hikvision camera |
| Hik test tool | activate Hikvision camera , Camera image test, support modify IP, user name and password etc parameters . |
| HD TVI camera test | Support resolution 720p 25fps,30fps,50fps,60fps / 1080P 25fps,30fps , camera OSD menu control over coaxial cable |
| CVBS Video Signal test | 1 channel Video IN BNC input,1 channel Video OUT BNC output,support PAL/NTSC |
| Zoom Image | Support Analog camera and IP camera image zoom /move |
| Snapshot, video record and playback | Image Screen snapshot, record ,save ,view and record and play back |
| PoE power output | 48V PoE power output,Max power 24W |
| 12V/2A power output | Output DC12V/2A power for camera |
| Audio test | 1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone |

| | |
|-----------------------|---|
| PTZ control | Support RS232/RS485 control, Baud 600-115200bps, Compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, Lilin, Yaan, etc |
| color bar generator | Output one channel PAL/NTSC color bar video signal for testing monitor or video cable.(red, green ,blue, white and black color) |
| UTP Cable tester | Test UTP cable connection status and display on the screen. Read the number on the screen |
| Data monitor | Captures and analyzes the command data from controlling device,also can send hexadecimal |
| Network test | IP address scan, link test, Ping test, Quickly search the connection IP camera and other device's IP address |
| PoE/PSE test | Measurement POE switch or PSE power supply voltage and cable connection status |
| POWER | |
| External power supply | DC 12V (2A) |
| Battery | Built-in 7.4V Lithium polymer battery , 5000mAh |
| Rechargeable | After charging 7~8 hours, normal working time 16 hours |
| Parameter | |
| Operation setting | Capacitive touch screen, OSD menu,Chinese/English |
| Auto off | 5-30 (mins) |
| General | |
| Working Temperature | -10℃---+50℃ |
| Working Humidity | 30%-90% |
| Dimension/Weight | 212mm×135.5mm×56.5mm / 0.75Kg |