



Durio 532A Malaysia Prihatin 3 Ply Protective Face Mask

| Product Specification | | | |
|-------------------------------|--|-----------------------------------|---|
| Product Name | Durio 532A Malaysia Prihatin 3 Ply Protective Face Mask | | |
| Protection Level | >95% Particle Filtration Efficiency 0.3 µm PFE (NIOSH 42 CFR 84) >99% Bacteria Filtration Efficiency 3.0 µm BFE (EN 14683:2019 Annex B) | | |
| Breathability Resistance (ΔP) | ≤ 3.0 mmH ₂ O/cm ² (EN 14683:2019 Annex C) | | |
| Fluid Resistance | 16 kPa (ISO 22609:2004) | | |
| Sterilization | Non-Sterile | | |
| Cleanliness | ≤30 cfu/g (ISO 11737-1:2018) | | |
| Technology | Electrostatically Charged Melt Blown Filter Media | | |
| Intended Use | Disposable device that covers the user's nose and mouth and provides a physical barrier to droplets, fluids, bacteria and particulate materials. | | |
| Design | Ear Loop Type | | |
| Dimension | 175mm x 95mm | | |
| Use Limitation | Single Use | | |
| Composition | Outer Layer | Material | Printed PP Non-Woven Fabric |
| | | Type | Hydrophobic Spunbond |
| | | Color | Malaysia Prihatin Printing Icon |
| | Middle Filtration Layer | Material | PP Non-Woven Fabric |
| | | Type | Electrostatically Charged Melt Blown |
| | | PFE | > 95% |
| | | BFE | > 99% |
| | Inner Layer | Color | White |
| | | Material | PP Non-woven Fabric |
| | | Type | Hydrophilic Thermalbond |
| | Ear Loop | Color | White |
| | | Material | Polyester Covered Spandex Yarn |
| | | Design | 4mm Flat |
| | | Fixed Way | Ultrasonic Welding to Outer Layer of the Protective Face Mask |
| Nose Strip | Color | White | |
| | Material | Zinc Electro Galvanized Iron Wire | |
| | Design | Extra Long & Adjustable | |
| | Location | Centre of The Upper Part of Mask | |
| | | Color | White |



Durio 532A Malaysia Prihatin 3 Ply Protective Face Mask

| Packing & Storage | |
|--------------------------------------|---|
| Inner Box | |
| Brand | Durio |
| Size | 220mm x 100mm x 100mm |
| Weight | 246g ± 5% |
| Carton Box | |
| Size | 515mm x 450mm x 520mm |
| Weight | 13.38kg ± 5% |
| Packing Details | |
| Inner | 50 pcs per box |
| Carton | 50 boxes per carton |
| Recommended Storage Condition | |
| Temperature | < 40°C (104 °F) |
| Humidity | < 80% RH |
| Environment | Store in the original packaging, away from contaminated areas, dust, sunlight and damaging chemicals. |
| Shelf Life | 3 Years from date of Manufacture |
| Caution | Not designed for use as protection against any toxic dust, chemicals, gases, or vapors. |