

LED Street Light With Philips Chips

APPLICATION
Parking Areas, Stadiums, Pathway, Garden,
Commercial and Residential Areas.

- FEATURES**
- Built-In IC TECHNOLOGY
 - Over temperature protection
 - Filtered waveform, Stable voltage
 - High system Efficiency
 - Thin & light weight size

- LUMINAIRE SPECIFICATION**
- Color Temperature : 3000K/5000K
 - Color Rendering Index : ≥ 70
 - Lifetime : 50,000Hrs
 - Beam Angle : $140^\circ \times 70^\circ$
 - Voltage : AC85-265V 50/60Hz
 - Working Temperature : $-20^\circ\text{C} \sim 50^\circ\text{C}$
 - Fitting Material : Die-Cast Aluminium
 - Diffuser : PC
 - IP Protection Level : IP65
 - Surge Protection : 10KV
 - Light Emitting Diode : Philips SMD 3030
 - Recommend height : 50W (3-5m)
: 100W (5-7m)
: 150W (7-9m)
: 200W (9-11m)
 - Pole / Arm Diameter : 50W ($\varnothing 40$ -50mm)
: 100W ($\varnothing 45$ -60mm)
: 150W ($\varnothing 45$ -60mm)
: 200W ($\varnothing 45$ -60mm)



Model	Power (W)	Input Voltage (V)	CCT (K)	Lumen (lm)	Size L x W x H (mm)	Quantity of LED	Net Weight	Packing
BSSL-1050	50W	AC85~265	3000/5000	6000	400 x 140 x 50	60 pcs	1.0 kg	15/CTN
BSSL-1100	100W	AC85~265	3000/5000	12000	530 x 182 x 50	120 pcs	1.5 kg	10/CTN
BSSL-1150	150W	AC85~265	3000/5000	18000	620 x 187 x 50	180 pcs	2.3 kg	8/CTN
BSSL-1200	200W	AC85~265	3000/5000	24000	650 x 220 x 50	240 pcs	2.9 kg	6/CTN