BSLight




RECESSED T-BAR PRISMATIC **DIFFUSED FITTING (Imperial Size)**



APPLICATION

• Mainly Used for General Lighting in Office, Hypermarket, Hospital, Complex.





FEATURES

| ТҮРЕ | T-Bar Prismatic Diffused Fitting (Imperial Size) | | | |
|-----------------------------|--|--|--|--|
| MODEL/CODE | BSC | | | |
| BODY | High Quality Gauge Sheet Steel | | | |
| PAINT WORK | Fully Coated With Epoxy Powder Coated Finished | | | |
| MOUNTING | Recessed Type | | | |
| LIGHT SOURCE | Fluorescent TLD Lamp and T8 LED Tube | | | |
| LAMP HOLDER & STARTERHOLDER | Polycarbonate Material | | | |
| COMPONENT | Conventional or Electronic Ballast, EL Emergency Power Pack, Fused Terminal Block | | | |

| MODEL | Number Of Lamp | L (mm) | L1 (mm) | W (mm) | H (mm) |
|-------------------|----------------|-----------|------------|-----------|-----------|
| BSC 220 (1' x 2') | 2 x 2 feet | 612 | 600 | 298 | 90 |
| BSC 220 | 2 x 2 feet | 612 | 600 | 605 | 90 |
| BSC 320 | 3 x 2 feet | 612 | 600 | 605 | 90 |
| BSC 420 | 4 x 2 feet | 612 | 600 | 605 | 90 |
| BSC 240 (1' x 4') | 2 x 4 feet | 1222 | 1210 | 298 | 90 |
| BSC 240 | 2 x 4 feet | 1222 | 1210 | 605 | 90 |
| BSC 340 | 3 x 4 feet | 1222 | 1210 | 605 | 90 |
| BSC 440 | 4 x 4 feet | 1222 | 1210 | 605 | 90 |