
BSLight



RECESSED T-BAR PRISMATIC DIFFUSED **HINGED FRAME FITTING (Imperial Size)**

APPLICATION

• Mainly Used for Technical Workshop, Hospital, Laboratories, Food Insdutry, Office and Supermarket.





FEATURES

ТУРЕ	Recessed T-Bar Prismatic Diffused Hinged Frame Fitting (Imperial Size)			
MODEL/CODE	BSC/HF (Recessed Hinged Frame)			
BODY	High Quality Gauge Sheet Steel			
PAINT WORK	Fully Coated With Epoxy Powder Coated Finished			
MOUNTING	Recessed Type			
LIGHT SOURCE	Fluorescent TLD Lamp and T8 LED Tube			
LAMP HOLDER & STARTERHOLDER	Polycarbonate Material			
COMPONENT	Conventional or Electronic Ballast, EL Emergency Power Pack, Fused Terminal Block			

MODEL	Number Of Lamp	L (mm)	L1 (mm)	W (mm)	H (mm)
BSC/HF 220 (1' x 2')	2 x 2 feet	612	600	298	85
BSC/HF 220	2 x 2 feet	612	600	605	85
BSC/HF 320	3 x 2 feet	612	600	605	85
BSC/HF 420	4 x 2 feet	612	600	605	85
BSC/HF 240 (1' x 4')	2 x 4 feet	1222	1210	298	85
BSC/HF 240	2 x 4 feet	1222	1210	605	85
BSC/HF 340	3 x 4 feet	1222	1210	605	85
BSC/HF 440	4 x 4 feet	1222	1210	605	85