## **BSLight**




## SURFACE MOUNTED PRISMATIC DIFFUSER WITH HINGED FRAME



## **APPLICATION**

• Mainly Used for Technical Workshop, Laboratories, Food Industry, Office and Supermarket.





## **FEATURES**

ТҮРЕ	Surface Mounted DiffusedWith Hinged Frame			
MODEL/CODE	BM/HF (Surface Hinged Frame)			
BODY	High Quality Gauge Sheet Steel			
PAINT WORK	Fully Coated With Epoxy Powder Coated Finished			
MOUNTING	Surface Type			
LIGHT SOURCE	Fluorescent TLD Lamp and T8 LED Tube			
LAMP HOLDER & STARTERHOLDER	Polycarbonate Material			
COMPONENT	Conventional or Electronic Ballast, EL Emergency Power Pack, Fused Terminal Block			

MODEL	Number Of Lamp	L (mm)	W (mm)	H (mm)
BM/HF 220 (1' x 2')	2 x 2 feet	612	298	85
BM/HF 220	2 x 2 feet	612	603	85
BM/HF 320	3 x 2 feet	612	603	85
BM/HF 420	4 x 2 feet	612	603	85
BM/HF 240 (1' x 4')	2 x 4 feet	1222	298	85
BM/HF 240	2 x 4 feet	1222	603	85
BM/HF 340	3 x 4 feet	1222	603	85
BM/HF 440	4 x 4 feet	1222	603	85