

Reflector Reflector

U-LI Goodlite's range of reflectors is specially designed for directional light control. It can be easily added on to bare batten for symmetrical or asymmetrical light distribution. It is available in epoxy powder coated and oven baked or high reflectance aluminium mirror.

Focusing light to areas required.

Shield bright illumination from normal view angles.

Easy attachment to standard batten fittings.

Dimension of Fittings

Model	Wattage (Tubes)	Length	Profile
GMR 120	1 x 18W	610 mm	<p>Metal Aluminium</p>
GMR 140	1 x 36W	1220 mm	
GMR 158	1 x 58W	1520 mm	
GMR 170	1 x 70W	1820 mm	
GMR 220	2 x 18W	610 mm	
GMR 240	2 x 36W	1220 mm	
GMR 258	2 x 58W	1520 mm	
GMR 270	2 x 70W	1820 mm	
GMR 120/H	1 x 18W	610 mm	
GMR 140/H	1 x 36W	1220 mm	
GMR 158/H	1 x 58W	1520 mm	
GMR 170/H	1 x 70W	1820 mm	
GMR 220/H	2 x 18W	610 mm	
GMR 240/H	2 x 36W	1220 mm	
GMR 258/H	2 x 58W	1520 mm	
GMR 270/H	2 x 70W	1820 mm	

For Ordering

/AR : Add /AR for Aluminium Mirror Reflector



Accessories / Options



GLC 91



GLC SL



GLC CLK



GLC DC



AR Reflector