

## LED FLEXIBLE STRIP LIGHT GFS/L1/072/830(840)(865)



### Features

- Bright Build-in LED with **76 lm/W** efficacy.
- **Energy Saving** with Low-Power LED Flexible Strip.
- **Flexible LED** strips can be curved around the corners, trimmed and connected to any required length.
- **Easy Installation** with Simple Mounting and Connection.
- **High Quality SMD LED.**
- **Ideal Choice** for Decoration.

### Applications

- Multi Purpose Usage Domestic, Commercial & Industrial
- Building, Office, School, Hospital, Retail Outlet, Supermarkets
- Cove Lighting, Cabinet Lighting, Signage, Architecture Lighting

### LIGHT SOURCE/OPTIC SPECIFICATION

LED Type	SMD 2835
Power Consumption	7.2W
Luminaire Flux	550 lm/M
CRI	Ra≥ 80
CCT	3000K, 4000K, 6500K
Lifetime, L <sub>70</sub>	20,000 h

### ELECTRICAL SYSTEM

Power Consumption	7.2W
Input Voltage	220-240Vac, 50/60Hz
Power Factor	≥ 0.9
DC Input	12V
Dimmable	NIL
Classification	IP20

### PRODUCT DESCRIPTION

Ordering Model	Power (W)	Lumen (lm/M)	Voltage (V/DC)	CCT (K)	Beam Angle (°)
GFS L1/072/830	7.2W	550 lm	12V	3000K	120°
GFS L1/072/840	7.2W	550 lm	12V	4000K	120°
GFS L1/072/865	7.2W	550 lm	12V	6500K	120°

### PHOTOMETRY

