





ECO SFB2 Slim Batten Series



Features

Ultra slim base width with integrated LED Tube. Offering easy of installation and quality of light


Application

 $\label{thm:continuous} \textbf{Suitable for general lighting, industrial and domestic areas.}$

Luminaire Product Description

Mounting	Surface/Wall/Pendant		
Housing Material	Cold Roll Steel		
Coating	Epoxy Polyester Powder		
Light Source	SJLITE ECO Glass Tube HO		
Input Voltage	240V~, 50Hz		
Power Factor	>0.9		
Ingress Protection	IP20		
Insulation Classification	Class I		

Wiring Diagram




Control

*Dimming Option Fixed Output



Dimension



Order Reference

Model	Quantity Of Tube	Length Of Tube	Example:
ECO SFB2	1 2	A (2ft) C (4ft)	ECO SFB2 1A 120 — ECO SFB2 1 A 1 20 Length OfTube Quantity OfTube Quantity OfTube Quantity OfTube

Order Information

Model No.	No. Of Lamp	L(mm)	L1(mm)	W(mm)	W1(mm)	H(mm)	H1(mm)	
ECO SFB2 1A 120	1	614	614		51		61	
ECO SFB2 2A 220	2		_	100	_	66	_	
ECO SFB2 1C 140	1	1223		51		61		
ECO SFB2 2C 240	2		1223		100		66	

Note : Subject to +/- 1.5mm

*Other various types are available upon request.