





ECO SAC T8 Mirror Optic Louvre Fitting Series (Surface)

Features

Designed for direct mounting to ceiling with single parabolic mirror optic louvre with christmas profile cross blades. Louvre reflection by means of slide lock set and can be lowered and hang from either side.

Application

Mainly used for general lighting in offices, supermarkets and complexes.


Luminaire Product Description

Surface
Cold Roll Steel
Epoxy Polyester Powder
SJLITE ECO Glass Tube HO
240V~, 50Hz
>0.9
IP20
Class I

Optics

Louvre Material	High Quality Anodised Aluminium
Louvre Type	Specular

Wiring Diagram



Control

*Dimming Option	Fixed Output	
-----------------	--------------	--



Dimension

			н
		I	
1	W		

Order Reference

Model	Quantity Of Tube	Length Of Tube
ECO SAC	1	A (2ft)
	2	C (4ft)
	3	
	4	

Example:	
ECO SAC 2C 240 - E	CO SAC 2 C 2 40
Model No.	Length Of Tube Quantity Of Tube Length Of Tube Quantity Of Tube

Order Information

Model No.	No. Of Lamp	L(mm)	L1(mm)	W(mm)	W1(mm)	H(mm)	H1(mm)
ECO SAC 2A 220/S MOL	2	612		598			
ECO SAC 2C 240/S MOL (1x4)	2	1222		302	_	90	-
ECO SAC 2C 240/S MOL	2		59	598			
ECO SAC 3C 340/S MOL	3			396			

Note : Subject to +/- 1.5mm

 ${}^{\star}\text{Other}$ various types are available upon request.