



MASTER Plastic LEDcandles & lusters

MASTER LEDcandle DT 4-25W E14 B38 CL_AP

The MASTER Plastic LEDcandle & luster range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to incandescent lamps. They are particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E14 holder for candles and E14 and E27 holders for lusters. MASTER Plastic LEDcandle & luster deliver huge energy savings of up to 80% compared with traditional incandescent lamps and provides excellent quality of light. By offering a lifetime of 25,000 hours it lowers maintenance costs. They can be used together with most leading-edge dimmers, enabling further efficiencies while helping to create the desired atmosphere.

Product data

| General information | |
|---------------------------------|-------------------------------|
| Cap-Base | E14 [E14] |
| EU RoHS compliant | Yes |
| Nominal Lifetime (Nom) | 25000 h |
| Switching Cycle | 50000 |
| Technical Type | 4-25W |
| Light technical | |
| Color Code | 822-827 [tunable warm white] |
| Luminous Flux (Nom) | 250 lm |
| Color Designation | Warm White (WW) |
| Luminous Efficacy (rated) (Nom) | 65 lm/W |
| Color Consistency | <6 |
| Color Rendering Index (Nom) | 80 |

| LLMF At End Of Nominal Lifetime (Nom) 70 % | |
|--|--------------------|
| Operating and electrical | |
| Input Frequency | 50 to 60 Hz |
| Power (Nom) | 4 W |
| Lamp Current (Nom) | 25 mA |
| Wattage Equivalent | 25 W |
| Starting Time (Nom) | 0.5 s |
| Warm Up Time to 60% Light (Nom) | instant full light |
| Power Factor (Nom) | 0.7 |
| Voltage (Nom) | 220-240 V |

MASTER Plastic LEDcandles & lusters

| | |
|-------------------------------|-------|
| Temperature | |
| T-Case Maximum (Nom) | 85 °C |
| Controls and dimming | |
| Dimmable | Yes |
| Mechanical and housing | |
| Bulb Finish | Clear |
| Bulb Shape | B38 |
| Approval and application | |
| Suitable For Accent Lighting | No |
| Energy Consumption kWh/1000 h | 4 kWh |

| | |
|---------------------------------|---|
| Product data | |
| Full product code | 871869645372800 |
| Order product name | MASTER LEDcandle DT 4-25W E14 B38 CL_AP |
| EAN/UPC - Product | 8718696453728 |
| Order code | 929001139808 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 10 |
| Material Nr. (12NC) | 929001139808 |
| Net Weight (Piece) | 0.063 kg |

Dimensional drawing



| Product | D | C |
|---|-------|--------|
| MASTER LEDcandle DT 4-25W E14 B38 CL_AP | 38 mm | 113 mm |

MASTER LEDcandle DT 4-25W E14 B38 CL_AP

Photometric data



MASTER Plastic LEDcandles & lusters

