

Conventional Tubes

Lifemax TL-D Standard Color

Standard specifications

Lifetime

10,000 hrs

Color temp

Available in

Cool daylight (6500K)



| | | |
|-----------------------|--------|--------|
| Wattage | 18W | 36W |
| Lumen | 1050lm | 2500lm |
| Base | G13 | G13 |
| Dimension (ft) | 2 | 4 |

TL-D Super 80

Benefits

- High initial light output compared with standard colors
- Can be used with conventional or electronic gear
- Relatively high efficacy, both initially and during lamp lifetime, with high lumen maintenance

Standard specifications

Lifetime

15,000 hrs

Color temp

Available in

Warm white (2700K & 3000K),

Cool white (4000K) &

Cool daylight (6500K)



| | | |
|-----------------------|-----|-----|
| Wattage | 18W | 36W |
| Base | G13 | G13 |
| Dimension (ft) | 2 | 4 |

Essential TL5

Benefits

- Comfortable working and living ambiances with CRI more than 80
- Provides highly reliable and high quality lighting solution at low cost
- Suitable for use at locations where need compact, high efficient, energy saving lighting

Standard specifications

Lifetime

15,000 hrs

Color temp

Available in

Warm white (3000K),

Cool white (4000K) &

Cool daylight (6500K)



| | | | |
|----------------|---|---|---------------------|
| Wattage | 14W | 21W | 28W |
| Lumen | 1350lm ¹ 1351lm ² 1260lm ³ | 2100lm ¹ 2101lm ² 1900lm ³ | 2900lm ⁴ |
| Base | G5 | G5 | G5 |

TL-D Starter

Benefits

- Switch starters for igniting fluorescent lamps with electromagnetic ballast 2-pin igniter in plastic (flame-retardant polycarbonate) canister
- Radio-interference suppression capacitor



| | | |
|---------------------|---------|---------|
| Product code | S2 | S10 |
| Wattage | 4 - 22W | 4 - 65W |

¹ Only available in 3000K. ² Only available in 4000K. ³ Only available in 6500K.

⁴ Only available in 3000K & 4000K.