

Product datasheet

Specifications



ZENcelo -10A Full-Flat Bell Switch-white

E8431PR1_WE

Training Objectives : Compliant

Main

Range	ZENcelo
Product or component type	Switch
Load type	Inductive Resistive Incandescent lamp Fluorescent lamp
Colour tint	White
Cover frame colour tint	White

Complementary

Device mounting	Surface Flush
Switch function	Bell push switch
Rated current	10 A at 250 V AC 50/60 Hz
Local signalling	Mechanical indicator (amber)
Number of gangs	1 gang
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	31 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 SS 227-1 EN 60669-1 GB 16915.1 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	87.2 g
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	4800
Package 2 Weight	573560.0 g
Package 2 Height	120 cm
Package 2 Width	120 cm
Package 2 Length	80 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	9476.0 g
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)