



### Main

Range	ZENcelo
Product or component type	Switch
Number of gangs	1 gang

### Complementary

Device mounting	Surface Flush
Rated current	20 A at 250 V AC 50/60 Hz
Material	Grid plate: polycarbonate + GF 20 % Base: polycarbonate Cover: polycarbonate Surround: polycarbonate Dolly: polycarbonate
Load type	Inductive
Cover frame colour tint	White
Connections - terminals	Brass rod terminals
Embedding depth	23 Mm
Width	87 Mm
Height	87 Mm
Depth	31.5 Mm

### Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	MS IEC 60669-1 BS EN 60669-1 IEC 60669-1 GB 16915.1 SS 227-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	124.0 G
Package 1 Height	3.34 Cm
Package 1 Width	8.6 Cm

Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.341 Kg
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	8.528 Kg
Package 3 Height	21 Cm
Package 3 Width	30 Cm
Package 3 Length	39.5 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Product Life Status : **Commercialised**