

# Product datasheet

Specifications



## 45A Double Pole Switch and 13A Switched Socket Outlet, Silver Satin

E84T15D45N\_SA

### Main

Product or component type	Power socket-outlet
Load type	No inductive load
Cover frame colour tint	Silver satin
Cover plate colour tint	Grey

### Complementary

Device mounting	Surface Flush
Switch function	2-pole
Rated current	45 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Control circuit: polycarbonate surround Brass contact Phosphor contact Polycarbonate base Polycarbonate grid plate
Connections - terminals	Folded terminal
Width	147 mm
Height	87 mm
Depth	8 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 4177
Standards	BS 4177

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	3.4 cm
Package 1 Width	8.7 cm
Package 1 Length	14.7 cm
Package 1 Weight	229.603 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)