

Product datasheet

Specifications



ZENcelo 13A 1Gang switched socket with neon White

E8415N_WE_G11

Main

Range	ZENcelo
Device application	Power supply
Product or component type	Power socket-outlet
Load type	Resistive
Colour tint	White
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Local signalling	Indicator light, neon (amber)
Switch function	1-pole
Clamping connection capacity	2 x 4 mm ² 3 x 2.5 mm ²
Rated current	13 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Brass contact Phosphor contact Polycarbonate base Polycarbonate grid plate Polycarbonate surround
Connections - terminals	Folded terminal
Width	87 mm
Height	87 mm
Depth	8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 1363-2 MS 589

Standards	MS 589 SS 145 BS 1363-2
------------------	-------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	140.414 g
Package 1 Height	2.7 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)