



Commercial status

End of Commercialisation : JUN 30, 2022

 End of Commercialisation

Main

Range	ZENcelo
Device application	Power supply
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E
Load type	Resistive
Colour tint	Silver bronze

Complementary

Device mounting	Flush Surface
Local signalling	Indicator light, neon (amber)
Clamping connection capacity	2 x 4 mm ² 3 x 2.5 mm ²
Rated current	13 A at 250 V AC 50 Hz
Number of gangs	2 gangs
Material	Brass contact Polycarbonate base Polycarbonate grid plate Polycarbonate surround Phosphor bronze contact
Connections - terminals	Folded terminal
Width	147 Mm
Height	87 Mm
Depth	8 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 1363-2 MS 589 SS 145
Standards	SS 145 BS 1363-2 MS 589

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Product Life Status : **End of commerc. - Block**