



Main

Range	ZENcelo
Device application	Power supply
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E
Load type	No inductive load
Colour tint	Silver satin

Complementary

Device mounting	Surface Flush
Local signalling	On: mechanical indicator (amber) Off: mechanical indicator (white)
Clamping connection capacity	2 x 2.5 mm ²
Rated current	15 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Polycarbonate base Polycarbonate grid plate Polycarbonate surround
Connections - terminals	Folded terminal
Width	87 Mm
Height	87 Mm
Depth	8 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 546 MS 1577 SS 472
Standards	BS 546 MS 1577 SS 472

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	111.7 G
Package 1 Height	21 Cm
Package 1 Width	31 Cm
Package 1 Length	50 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Product Life Status : **Commercialised**