



Main

Range of product	ZENcelo
Product or component type	Telephone socket
Connector type	RJ11
Number of gangs	2 gangs
Cover frame colour tint	White

Complementary

Device mounting	Surface Flush
Socket additional information	Shuttered
Communication network category	Voice: 3
Rated current	1.5 A
Fixing mode	By screws M4 x 25 mm
Fixing center	60.3 mm
Material	Polycarbonate: housing
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Contact resistance	1 MOhm
Insulation resistance	>= 200 mOhm
Dielectric strength	1000 V for 60 s at 60 Hz
AWG gauge	AWG 26...AWG 22 (4 twisted pair cables)
Minimum return loss	23 DB
Embedding depth	22.2 Mm
Width	87 Mm
Height	87 Mm
Depth	30.4 Mm

Environment

Environmental characteristic	No UV resistant
Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Standards	TIA/EIA-568-B.2-1 ASTMD4566-98

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	80.0 G
Package 1 Height	1.52 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	901.0 G
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	5.886 Kg
Package 3 Height	21.5 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**