



Main

Range	ZENcelo
Product or component type	Data socket
Cover frame colour tint	Silver bronze
Socket additional information	Shuttered

Complementary

Rated current	1.5 A
Communication network category	Data: 5e
Insulation resistance	>= 200 mOhm
Contact resistance	1 MOhm
Number of gangs	2 gangs
Connector type	RJ45
Material	Polycarbonate housing
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
AWG gauge	AWG 26...AWG 22 (4 twisted pair cables)
Minimum return loss	23 DB
Device mounting	Flush Surface
Fixing mode	By screws M4 x 25 mm
Fixing center	60.3 mm
Width	87 Mm
Height	87 Mm
Depth	38.5 Mm
Embedding depth	30.3 Mm

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	80.0 G
Package 1 Height	1.52 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	901.0 G
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	5.886 Kg
Package 3 Height	21.5 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**